Product Description

00 00:	TMC202.
000 0 :	00 00 3D 00 00 00 00 00 00 00 00 00 00 00 00 00
000 00 :	□□ □□□ □□ □□ 200 □,□□ □□□ □□□□□. (ASTM F2413-18 M I / 75 C / 75, CE EN ISO 20345 □□)
00 00 :	□□ □□□ 1100 □□□ □□ □□□ □□ □□□ □□□ □□□□□□. (ASTM F2413-18 M I / 75 C / 75, CE EN ISO 20345 □□)
<u> </u>	CE EN ISO 20345 SB-P SRC [] [] []
<u> </u>	3d 00 00 00000
<u></u> :	
<u> </u>	
Sockliner :	00 000 00 00 0 0 0 EVA
:	
:	
:	37-46.
:	6. □□
<u></u> :	
	□□ □□ □ 1 □, □□ □ 10 □. □□ □□□ □□□□58.5 x 40 x 32.5 cm.
00000 000 :	3300pairs / 1x20 '\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \

Product Pictures





SAFETY SHOES TEST





Toecap Test≥200 Joules



Midsole Test≥1200 Newtons



ESD Anti-Static Test



Tear Strength ≥120N



Bondness Test ≥4.0N/mm



Flex Tester ≥ 36,000T

Canton Fair





SAFETY SHOES



RAIN BOOTS





PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY