

Product Description

اسم المنتج:	مكافحة ساكنة للماء أحذية السلامة التنفيذية المركبة اصبع القدم غير المعدنية للرجال
رقم العنصر:	M006
العلوي والوحيد:	الجزء العلوي: جلد مايكروفايبر كثافة مزدوجة PU / PU : الوحيد
إصبع قدم:	1. اصبع القدم المركب ليكون مقاومًا للصدمات 200 جول. 2. غير متوفرة أيضا.
ميدسولي:	1. النعال غير المعدنية المضادة للاختراق ل يكون ثقب مقاومة 1100 نيوتن. 2. عدم يكون أيضا قدمت
وزن:	كجم / العلاقات العامة 1.0
أسلوب:	لا دانتييل
بطانة:	جلد بولي يوريثان ناعم ، سيحافظ على راحة قدميك
النعال:	شبكة مصبوب أو غيرها + EVA
طوق واللسان:	جلد سنوكات
اعمال بناء:	PU حفن
ارتفاع:	كاحل منخفض
بحجم:	يورو 38-46
اساسي:	أو غيرها حسب متطلباتك CE EN ISO 20345 S3 SRC
ضمان:	اشهر 6
وظيفة:	مقاوم للانزلاق / الزيت / الصدمات / الثقب ، مضاد للكهرباء الساكنة ، مقاوم للماء ، خالي من المعدن
صفقة:	زوج لكل لون مربع ، 10 أزواج في الكرتون. حجم الورق المقوى: 32.5 × 40 × 58.5 سم 1
كمية تحميل الحاوية:	زوج / حاوية 1 × 20 قدمًا 3300 زوج / حاوية 1 × 40 بوصة 6600

Product Pictures





Company Information



Intertek

EC Type Examination Certificate



Issued to: FUJIAN HONGJIAN SHISEI CO., LTD.
SHANGHAI INDUSTRIAL ZONE, JINCHANG TOWN, NINGBO
321117, ZHEJIANG PROVINCE, CHINA

Authorised Representative: HANDESHI AND SAFETY PRODUCTS APLC (UK) LTD.
1201 Village, North Town, Jiangyin District, Suzhou,
Henan Province, China

Date of Issue: 13 January 2018

Expiry Date: 13 January 2020

Certificate No.: L20170002947 (extension of certificate L20170294719)

Product Reference(s): Safety Valve
48501-08602
48502-08604
48503-08606
48504-08608
48505-08610
800 300 300 300

Description:

Construction:	Iron/Steel
Threading:	Steel valve
Material:	Steel valve
Unit:	mm
Size:	800 (Supply)
Mount:	AC
Test Standard:	EN 10606 Part 1
Test Range:	30-45
Category:	800 Alfa

C.M.

Product Name: Safety Valve
Manufacturer: FUJIAN HONGJIAN SHISEI CO., LTD.
Address: SHANGHAI INDUSTRIAL ZONE, JINCHANG TOWN, NINGBO 321117, ZHEJIANG PROVINCE, CHINA

EU Declaration No.: 168/12018
EU Declaration No.: 168/12018



Production Process



Raw Materials



Punching



Cutting



Riveting



Eyeletting



Sewing



Heat - Setting



Molding



Making up



Finished Goods



Packing



Inspection

SAFETY SHOES TEST



Toecap Test ≥ 200 Joules



Midsole Test ≥ 1200 Newtons



ESD Anti-Static Test



Tear Strength ≥ 120 N



**Bondness Test
 ≥ 4.0 N/mm**



Flex Tester $\geq 36,000$ T

SHOES MATERIALS



Genuine Cow Leather



CE Steel Toecap



CE Steel Plate



Composite Toecap



Different Eyelets



Durable Lace



Breathable Lining



Comfortable Insoles



PU or RUBBER or TPU soles

Canton Fair



SAFETY SHOES



RAIN BOOTS



PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY