

Product Description

اسم المنتج:	رخيص الصلب تو أحذية سلامة العمل في الأماكن المغلقة الرجال
رقم العنصر:	SD3063
العلوي والوحيد:	العلوي: جلد البقر الحقيقي من جلد الغزال الوحيد: بو الكثافة المزدوجة
إصبع قدم:	1. غطاء إصبع القدم الصلب ، يمكن أن يكون تأثير مقاومة 200 جول . 2. غير المقدمة أيضا .
ميدسولي:	1. لوحة الصلب، يمكن أن يكون ثقب مقاومة 1100 نيوتن . 2. عدم يكون أيضا قدمت
وزن:	كلغ / العلاقات العامة 1.2
طوق:	عالية الكثافة النسيج أكسفورد مع الاسفنج
لسان:	النسيج عالية الكثافة أكسفورد
بطانة:	(برتقالي الهواء وشبكة النسيج الجاف (ستبقى قديمك الجافة ومريحة
Sockliner:	(المصبوب) (قلل إلى حد كبير من الألم والتعب من العمل اليومي PU أو HI-POLY أو EVA
اعمال بناء:	بو حقن
ارتفاع:	ارتفاع الكاحل
بحجم:	37-47 (3-13)
اساسي:	أو غيرها حسب الاحتياجات الخاصة بك CE EN ISO 20345 S1P SRC
ضمان:	اشهر 6
صفقة:	زوج لكل ج أولور مربع التعبئة الداخلية ، 10 أزواج في الكرتون 1
حجم الورق المقوى	سم 59 × 44 × 33
كمية حمولة الحاوية:	3200 حاويةpairs / 1x20 6400 حاويةpairs / 1x40

Product Pictures





Company Information





EC Type Examination Certificate

CE	<p>Issued to: FUJIAN HONGJIAN SHISECO LTD. SHANGHAI INDUSTRIAL ZONE, JIANGNAN TOWN, NANJI 3211, ZHUJIANG PROVINCE, CHINA</p> <p>Authorised Representative: HANDESHI SHIJIYI PRODUCTIONS APCL CO., LTD. 1301 Village, Zhuhai Town, Jiangyin District, Suzhou, Henanjiang Province, China</p> <p>Date of Issue: 11 January 2018</p> <p>Expiry Date: 11 February 2020</p> <p>Certificate No.: LDC170002947 (extension of certificate LDC170294794)</p> <p>Product Reference(s): Safety Plug: 4850V-3840V 4850V-3840V 4850V-3840V 4850V-3840V 850 320 350 350</p> <p>Description: <table border="0" style="width: 100%;"> <tr> <td>Construction:</td> <td>Insulation</td> </tr> <tr> <td>Terminal:</td> <td>Open contact</td> </tr> <tr> <td>Material:</td> <td>Open plug</td> </tr> <tr> <td>Color:</td> <td>White</td> </tr> <tr> <td>Size:</td> <td>850 320 350</td> </tr> <tr> <td>Mount:</td> <td>ACB</td> </tr> <tr> <td>Test Standard:</td> <td>EN 60898-1</td> </tr> <tr> <td>Test Range:</td> <td>38.4V</td> </tr> <tr> <td>Category:</td> <td>350 350</td> </tr> </table> </p>	Construction:	Insulation	Terminal:	Open contact	Material:	Open plug	Color:	White	Size:	850 320 350	Mount:	ACB	Test Standard:	EN 60898-1	Test Range:	38.4V	Category:	350 350
Construction:	Insulation																		
Terminal:	Open contact																		
Material:	Open plug																		
Color:	White																		
Size:	850 320 350																		
Mount:	ACB																		
Test Standard:	EN 60898-1																		
Test Range:	38.4V																		
Category:	350 350																		

For the full and complete text of this certificate, please refer to the certificate text on the Intertek website.

Intertek is a registered trademark of Intertek Group Limited. All rights reserved. © 2018 Intertek Group Limited.



C.M.

1587-02947

01/11/2018



EU

1587-02947

01/11/2018



Production Process



Raw Materials



Punching



Cutting



Riveting



Eyeletting



Sewing



Heat - Setting



Molding



Making up



Finished Goods



Packing



Inspection

Canton Fair



SAFETY SHOES



RAIN BOOTS



PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY