

## Product Description

اسم المنتج:	Puncutre مقاومة التآكل غير الصلب الصلب اصبع القدم
رقم العنصر:	TM3006.
العلوي والوحيد:	□□□□□ □□□□□ □□□ □□□□ □□□□□□ (□□□□ □□□□□ □□□□ □□) □□□□□□□ □□□□□□□ □□ □□□□□□□)
قبة اصبع القدم:	قبة اصبع القدم الصلب لتكون تأثير مقاوم 200 جول. (قياسي) (ASTM F2413-18 M I / 75 C / 75, CE EN ISO 20345) غير موجود أيضا.
منتصف الوحد:	لوحة الصلب لتكون ثقوب مقاومة 1100 نيوتن. (قياسي) (ASTM F2413-18 M I / 75 C / 75, CE EN ISO 20345) غير موجود أيضا.
وزن:	كغ / العلاقات العامة 1.20
اللون:	أسود
طوق:	جلد بو الاصطناعي
لسان:	جلد بو الاصطناعي
بطانة:	نسيج شبكة الهواء الناعم
Sockliner:	لينة مصبوب أيضا المغلفة مع نسيج شبكة
بناء:	أسمنت
ارتفاع:	انخفاض الكاحل
مقاس:	يورو 38-46
يضمن:	3. الشهور
وظيفة:	حمض / تأثير / ثقوب / مقاومة للتآكل، امتصاص الصدمات، مقاومة للماء ومكافحة ساكنة / L افي المتاحة.
صفحة:	زوج لكل مربع اللون، 10 أزواج في الكرتون. حجم الكرتون 32.5 × 40 × 58.5 سم 1
تحميل كمية الحاوية:	حاوية ' 1x20 3300pairs / حاوية ' 1x40 6600pairs /

## Product Pictures





# SAFETY SHOES TEST



**Toecap Test  $\geq 200$  Joules**



**Midsole Test  $\geq 1200$  Newtons**



**ESD Anti-Static Test**



**Tear Strength  $\geq 120$ N**



**Bondness Test  
 $\geq 4.0$ N/mm**



**Flex Tester  $\geq 36,000$ T**



# Canton Fair



## SAFETY SHOES



## RAIN BOOTS



PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY

# Production Process



Raw Materials



Punching



Cutting



Riveting



Eyeletting



Sewing



Heat - Setting



Molding



Making up



Finished Goods



Packing



Inspection