

Product Description

Model	2163
Material	Air mesh 3D fly knit fabric PU leather
Features	1. Steel toe cap 200 Joules 2. Slip resistant
Weight	1. Weight per pair 1100g 2. Weight per pair
Outsole	3D air mesh
Upper	PU
Midsole	metatomical EVA HI-POLY
Width	36-47
Standards	CE EN ISO 20345 SB-P SRC
Color	6 colors
Size	1 pair per box 10 pairs per carton 58.5 x 40 x 32.5 cm
Quantity	3300 pairs / 1x20" box 6600 pairs / 1x40" box

Product Pictures



200 JOULE
TOECAP



SLIP-
RESISTANT



SHOCK
ABSORPTION



ANTI-STATIC



PETROL AND
CHEMICAL
RESISTANT



ANTI-NAIL
MIDSOLE



OIL
RESISTANT









WHAT DO YOU WORRY ABOUT MOST ABOUT BUYING LABOR PROTECTION SHOES?

More and more patterns of labor protection shoes?
What's right for you?



WEAR LABOR PROTECTION SHOES WITH QUALITY PROBLEMS
IT ENDANGERS LIFE SAFETY IN SERIOUS CASES

MATERIAL DISPLAY

TIGER MASTER



FUNCTION DISPLAY

TIGER MASTER



The difference between European standard and ordinary

The European standard AN1 steel toe cap is wider than the national standard steel toe, which can reasonably protect the toes.

Do not squeeze or grind your feet.

ORDINARY

STANDARD STEEL HEAD

EASY TO RUST AND WEAR



EUROPEAN STANDARD

WIDEN AN1 STEEL HEAD

ANTI-RUST, WIDENING
WITHOUT GRINDING FEET



SAFETY SHOES TEST



Toecap Test ≥ 200 Joules



Midsole Test ≥ 1200 Newtons



ESD Anti-Static Test



Tear Strength ≥ 120 N



**Bondness Test
 ≥ 4.0 N/mm**



Flex Tester $\geq 36,000$ T

Production Process



Raw Materials



Punching



Cutting



Riveting



Eyeletting



Sewing



Heat - Setting



Molding



Making up



Finished Goods



Packing



Inspection