

Product Description

| | |
|----------|---|
| Material | 3D EVA |
| Color | 605 |
| Material | 3D EVA |
| Weight | 200g / pair ASTM F2413-18 M I / 75 C / 75 CE EN ISO 20345 |
| Weight | 1100g / pair ASTM F2413-18 M I / 75 C / 75 CE EN ISO 20345 |
| Weight | 0.72 kgs / pr |
| Weight | |
| Weight | 3D EVA |
| Weight | 3D EVA |
| Weight | |
| Weight | EVA HI POLY PU |
| Weight | |
| Weight | |
| Weight | 38-46 |
| Weight | 3 |
| Weight | |
| Weight | 1 pair / 10 pairs / 58.5 x 40 x 32.5 cm |
| Weight | 3300pairs / 1x20' pair 6600pairs / 1x40' pair |

Product Pictures











SAFETY SHOES TEST



Toecap Test ≥ 200 Joules



Midsole Test ≥ 1200 Newtons



ESD Anti-Static Test



Tear Strength ≥ 120 N



**Bondness Test
 ≥ 4.0 N/mm**



Flex Tester $\geq 36,000$ T

Canton Fair



SAFETY SHOES



RAIN BOOTS



PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY