

Product Description

00000	000000000000000000
000	708
000000	0000003D000000 000000
000	00000000200000000 ASTM F2413-18 M I / 75 C / 75 CE EN ISO 20345000 000000
000	00000000001100000000 ASTM F2413-18 M I / 75 C / 75 CE EN ISO 20345000 000000
000	0.80 kgs / pr
000	000000
00	3D“00”00“00”
00	3D“00”00“00”
000	00000000
000	00EVA HI POLY PU
000	000
000	00
000	0036-48
000	6 0
000	000/0/00/000000000000000000000000
00	000100001000000058.5 x 40 x 32.5 cm
00000000	3300pairs / 1x20'000 6600pairs / 1x40'000

Product Pictures











Production Process



Raw Materials



Punching



Cutting



Riveting



Eyeletting



Sewing



Heat - Setting



Molding



Making up



Finished Goods



Packing



Inspection

SAFETY SHOES TEST



Toecap Test ≥ 200 Joules



Midsole Test ≥ 1200 Newtons



ESD Anti-Static Test



Tear Strength ≥ 120 N



Bondness Test ≥ 4.0 N/mm



Flex Tester $\geq 36,000$ T

Canton Fair



SAFETY SHOES



RAIN BOOTS



PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY