

Product Description

□□□□	□□□□□□□□□□□□□□□□
□□□	801
□□□□□	□□□3D□□□□□□□□pu
□□□	□□□□□□□□□□□□□□200□□□ □ASTM F2413-18 M I/75 C/75□CE EN ISO 20345□□□ □□□□□□
□□□	□□□□□□□□□□□□□□1100□□□ □ASTM F2413-18 M I/75 C/75□CE EN ISO 20345□□□ □□□□□□
□□□	530□/□□
□□□	□□□□□
□□□	3D□□□□□
□□□	3D□□□□□
□□□	□□□□□□□□□□
Sockliner□	□□eva□hi-poly□pu
□□□	□□
□□□	□□□
□□□	38-46
□□□	3 □□
□□□	s□□/□/□□/□□/□□□□□□□□□□□□□□□□□□□□□□
□□□	□□□□□1□□□□□□10□□□□□□□□□□58.5 x 40 x 32.5□□
□□□□□□□□	3200pAirs /1x20'□□ 6400pAirs /1x40'□□

Product Pictures









Model













TIGER MASTER SAFETY SHOES



Production Process



Raw Materials



Punching



Cutting



Riveting



Eyeletting



Sewing



Heat - Setting



Molding



Making up



Finished Goods



Packing



Inspection

SAFETY SHOES TEST



Toecap Test ≥ 200 Joules



Midsole Test ≥ 1200 Newtons



ESD Anti-Static Test



Tear Strength ≥ 120 N



**Bondness Test
 ≥ 4.0 N/mm**



Flex Tester $\geq 36,000$ T

Canton Fair



SAFETY SHOES



RAIN BOOTS



PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY