

Product Description

| | |
|----------|---|
| Material | PU / PU |
| Model | BTA045 |
| Material | PU / PU |
| Weight | 200g |
| Standard | ASTM F2413-18 M I / 75 C / 75 CE EN ISO 20345 Non |
| Weight | 1100g |
| Standard | ASTM F2413-18 M I / 75 C / 75 CE EN ISO 20345 Non |
| | |
| Material | EVA |
| Material | HI-POLY |
| Material | PU |
| Material | PU |
| Material | 37-47 |
| Material | 6 |
| Material | s/ / / |
| Material | 1 10 58.5 x 40 x 32.5 |
| Material | 3300pairs / 1x20' 6600pairs / 1x40' |

Product Pictures







TIGER MASTER[®] SAFETY SHOES

<https://safetyshoesfactory.com>



COMPOSITE
TOE CAP



NON-METALLIC ANTI
PENETRATION MID SOLE



ANTI-STATIC
SHOE



METAL
FREE



SLIP RESISTANT
SOLE



HEEL ENERGY
ABSORPTION

CE



YOUR SAFETY IS OUR CONCERN!

Production Process



Raw Materials



Punching



Cutting



Riveting



Eyeletting



Sewing



Heat - Setting



Molding



Making up



Finished Goods



Packing



Inspection

SAFETY SHOES TEST



Toecap Test ≥ 200 Joules



Midsole Test ≥ 1200 Newtons



ESD Anti-Static Test



Tear Strength ≥ 120 N



Bondness Test ≥ 4.0 N/mm



Flex Tester $\geq 36,000$ T

Canton Fair



SAFETY SHOES



RAIN BOOTS



PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY