

Product Description

□□□□□	□□□□□□□□□□□□□□□□
□□□	DTA031B
□□□□□□	□□□□□□ PU / PU□□□□
□□□	□ □□□□□200□□□□ □ASTM F2413-18 M I / 75 C / 75□CE EN ISO 20345□□□□ □□□□Non□
□□□	□□□□1100□□□□□□□□ □ASTM F2413-18 M I / 75 C / 75□CE EN ISO 20345□□□□ □□□□Non□
□□□	□□□□□
□□	□□□□□□
□□	□□□□□□
□□□	□□□□□□
□□□	□□EVA□HI-POLY□PU
□□□	PU□□
□□□	□□37-47
□□□	6□□
□□□	□□□□□□□□□□□□□□□□
□□□	□□□/□/□□□□/□□□□□□□□□□□□□□□□
□□	□□□□1□□□□□10□□□□□□□□ 59 x 44 x 33□□
□□□□□□□□	3200pairs / 1x20'□□ 6400pairs / 1x40'□□

Product Pictures





Production Process



Raw Materials



Punching



Cutting



Riveting



Eyeletting



Sewing



Heat - Setting



Molding



Making up



Finished Goods



Packing



Inspection

SAFETY SHOES TEST



Toecap Test ≥ 200 Joules



Midsole Test ≥ 1200 Newtons



ESD Anti-Static Test



Tear Strength ≥ 120 N



**Bondness Test
 ≥ 4.0 N/mm**



Flex Tester $\geq 36,000$ T

Canton Fair



SAFETY SHOES



RAIN BOOTS



PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY