

□□□□	□□□□□□
□□□	8075Y
□□□□□□	PU□□□□□□PU□□□□□□
□□□	1.□□□□□□□□ □ASTM F2413-05 M I / 75 C / 75□CE ENISO 20345□□□□□ □□ □□□□□
	□□□2.□□□□□
□□□ □ □□□□□	1.□□□□□□□□ □ASTM F2413-05 M I / 75 C / 75□CE ENISO 20345□□□□□□□□□□□□□
	□□□2.□□□□
□□	□□□ □□□□□□
□□	□□□PU□□□□
□□	□□□□□□□□□□
□□□	□□□□□□
□□□	PU □□
□□□	□□□□
□□□	4-12□38-46□
□□□	3□□□□□□□□□□□□□□
□□	□□□□□□10□□□□□□□
□□□□	56x38x31.5cm □38-40□; 58.5x40x32.5cm□41-43□; 61x42x35cm□44-46□
□□□□□□□	3300□/ 1X20'□□□□ 8200□/ 1x40'HQ□□□□

□□□□□□□□








□□□□□□□□



□□□□□□□□



□□□□□□□□



□□□□□□□□

## Production Process



Raw Materials



Punching



Cutting



Sewing



Eyeleting



Riveting



Heat-setting



Molding



Making Up



Inspection



Packing



Finish Products