

Product Description

Modelo	XXXXXXXXXXXXXXXXXXXX
Artículo	TMC4001
Descripción	3D PU&air max
Material	200 ASTM F2413-18 M I / 75 C / 75 CE EN ISO 20345
Material	1100 ASTM F2413-18 M I / 75 C / 75 CE EN ISO 20345
Peso	0.84 kgs / pr
Color	
Forma	3D " " "
Forma	3D " " "
Material	
Material	EVA HI POLY PU
Material	
Material	
Material	38-46
Material	6
Material	/ / /
Material	1 10 58.5 x 40 x 32.5 cm
Material	3300pairs / 1x20' 6600pairs / 1x40'

Product Pictures

NEW
0.42kg/pc





Production Process



Raw Materials



Punching



Cutting



Riveting



Eyeletting



Sewing



Heat - Setting



Molding



Making up



Finished Goods



Packing



Inspection

SAFETY SHOES TEST



Toecap Test ≥ 200 Joules



Midsole Test ≥ 1200 Newtons



ESD Anti-Static Test



Tear Strength ≥ 120 N



**Bondness Test
 ≥ 4.0 N/mm**



Flex Tester $\geq 36,000$ T

Canton Fair



SAFETY SHOES



RAIN BOOTS



PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY