

□□□□	PVC□□□□□□
□□□	098JFR
□□□□□	□□□□ □□□□PVC□□□□□□
□□□	1.□□□□□□□□ □ASTM F2413-05 M I / 75 C / 75□CE ENISO 20345□□□□□□ □□ □□□□□
	□□□2.□□□□□
□□□ □ □□□□□	1.□□□□□□□□ □ASTM F2413-05 M I / 75 C / 75□CE ENISO 20345□□□□□□□□□□□□
	□□□2.□□□
□□	PU□□□□□□□□
□□	□□□PU
□□	□□□
□□□	□□□□□
□□□	PVC □□
□□□	□□□□□
□□□	4-12□38-46□
□□□	3□□□□□□□□□□□□
□□	□□□□□□10□□□□□□
□□□□	56x38x31.5cm □38-40□; 58.5x40x32.5cm□41-43□; 61x42x35cm□44-46□
□□□□□□□	3300□/ 1X20'□□□ 8200□/ 1x40'HQ□□□

□□□PVC□□□□□□








□□□□□□□□





□□□□□□□□



PVC□□□□□□□□

## Production Process



Raw Materials



Punching



Cutting



Sewing



Eyeleting



Riveting



Heat-setting



Molding



Making Up



Inspection



Packing



Finish Products