

Product Description

Model	SD3060
Material	100% PU
Weight	1. 200g/pair 2. non
Dimensions	1. 1100 2. 1100
Thickness	1.2mm
Color	PU
Material	PU
Material	EVA/PU
Material	PU
Material	PU
Material	37-47/3-13
Material	CE EN ISO 20345 S1P SRC
Material	6
Material	10
Dimensions	59 x 44 x 33
Quantity	3200pairs / 1x20' 6400pairs / 1x40'

Product Pictures





Company Information



Intertek

EC Type Examination Certificate

CE	<p>Issued to: FUJIAN HONGJIAN SHISEI CO., LTD. SHANGHAI INDUSTRIAL ZONE, JIANGNAN TOWN, NINGBO 321117, ZHEJIANG PROVINCE, CHINA</p> <p>Authorised Representative: HANDESHI SHANGHAI SAFETY PRODUCTS MFG. CO., LTD. 1-101 Village, Xujiao Town, Jiangyin District, Suzhou, Henan Province, China</p> <p>Date of Issue: 11 January 2018</p> <p>Expiry Date: 11 February 2020</p> <p>Certificate No.: L26170002947 (extension of certificate L26170004199)</p> <p>Product Reference(s): Safety Plug: 480V 10A/15A 480V 10A/20A 480V 10A/25A 480V 10A/30A 50V 20A 15W-30W</p> <p>Description: <table border="0"> <tr> <td>Construction:</td> <td>Insulation</td> </tr> <tr> <td>Terminal:</td> <td>Open contact</td> </tr> <tr> <td>Material:</td> <td>Open slot</td> </tr> <tr> <td>Lead:</td> <td>2000</td> </tr> <tr> <td>Wire:</td> <td>6000 (PVC)</td> </tr> <tr> <td>Mount:</td> <td>ACB</td> </tr> <tr> <td>Test frequency:</td> <td>See national file</td> </tr> <tr> <td>Test range:</td> <td>20-40</td> </tr> <tr> <td>Category:</td> <td>009-014</td> </tr> </table> </p> <p>Authorised Representative: HANDESHI SHANGHAI SAFETY PRODUCTS MFG. CO., LTD. 1-101 Village, Xujiao Town, Jiangyin District, Suzhou, Henan Province, China</p> <p>Intertek Representative: Intertek (UK) Ltd, 3501 Market Street, Leicester, LE4 9AT, UK</p> <p>Signature: <i>C.M.</i> 16/1/2018</p> <p>Signature: <i>[Signature]</i> 16/1/2018</p> <p>Printed Name: Intertek (UK) Ltd, 3501 Market Street, Leicester, LE4 9AT, UK</p>	Construction:	Insulation	Terminal:	Open contact	Material:	Open slot	Lead:	2000	Wire:	6000 (PVC)	Mount:	ACB	Test frequency:	See national file	Test range:	20-40	Category:	009-014
Construction:	Insulation																		
Terminal:	Open contact																		
Material:	Open slot																		
Lead:	2000																		
Wire:	6000 (PVC)																		
Mount:	ACB																		
Test frequency:	See national file																		
Test range:	20-40																		
Category:	009-014																		

EU

This certificate is issued under the provisions of the EU Low Voltage Directive (LVD) 2006/95/EC and the EU EMC Directive (EMC) 2004/108/EC. It is valid for the products listed in the table above. The holder of this certificate is responsible for ensuring that the products covered by this certificate comply with the relevant EU Directives.



Production Process



Raw Materials



Punching



Cutting



Riveting



Eyeletting



Sewing



Heat - Setting



Molding



Making up



Finished Goods



Packing



Inspection

Canton Fair



SAFETY SHOES



RAIN BOOTS



PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY