

Product Description

CE	CE
SMR10	SMR10
PU / PU	PU / PU
200	200 ASTM F2413-18 M I / 75 C / 75 CE EN ISO 20345 Non
1100	1100 ASTM F2413-18 M I / 75 C / 75 CE EN ISO 20345 Non
CE	CE
EVA HI-POLY PU	EVA HI-POLY PU
PU	PU
38-46	38-46
6	6
s/ /	s/ /
10 58.5 x 40 x 32.5	10 58.5 x 40 x 32.5
3200pairs / 1x20' 6400pairs / 1x40'	3200pairs / 1x20' 6400pairs / 1x40'

Product Pictures





Production Process



Raw Materials



Punching



Cutting



Riveting



Eyeletting



Sewing



Heat - Setting



Molding



Making up



Finished Goods



Packing



Inspection

SAFETY SHOES TEST



Toecap Test ≥ 200 Joules



Midsole Test ≥ 1200 Newtons



ESD Anti-Static Test



Tear Strength ≥ 120 N



**Bondness Test
 ≥ 4.0 N/mm**



Flex Tester $\geq 36,000$ T

Canton Fair



SAFETY SHOES



RAIN BOOTS



PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY