

Product Description

| | |
|----------|---|
| Model | SMR10H |
| Material | PU / PU |
| Weight | 200g |
| Standard | ASTM F2413-18 M I / 75 C / 75 CE EN ISO 20345 Non |
| Weight | 1100g |
| Standard | ASTM F2413-18 M I / 75 C / 75 CE EN ISO 20345 |
| Weight | CE |
| Weight | |
| Weight | |
| Weight | |
| Weight | EVA HI-POLY PU |
| Weight | PU |
| Weight | |
| Weight | 38-46 |
| Weight | 6 |
| Weight | s/ / / |
| Weight | 1 10 59 x 44 x 33 |
| Weight | 3200pairs / 1x20' 6400pairs / 1x40' |

Product Pictures





Production Process



Raw Materials



Punching



Cutting



Riveting



Eyeletting



Sewing



Heat - Setting



Molding



Making up



Finished Goods



Packing



Inspection

SAFETY SHOES TEST



Toecap Test ≥ 200 Joules



Midsole Test ≥ 1200 Newtons



ESD Anti-Static Test



Tear Strength ≥ 120 N



**Bondness Test
 ≥ 4.0 N/mm**



Flex Tester $\geq 36,000$ T

Canton Fair



SAFETY SHOES



RAIN BOOTS



PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY