

Product Description

Material	Non-slip
Model	SP026
Material	3D PU / PU
Weight	200g ASTM F2413-18 M I / 75 C / 75 CE EN ISO 20345 Non-slip
Weight	1100g ASTM F2413-18 M I / 75 C / 75 CE EN ISO 20345 Non-slip
Material	Non-slip
Material	3D PU
Material	Non-slip
Material	Non-slip
Material	EVA HI-POLY PU
Material	PU
Material	Non-slip
Material	38-46
Material	6
Material	s/ / /
Material	10 58.5 x 40 x 32.5
Material	3200pairs / 1x20' 6400pairs / 1x40'

Product Pictures





Production Process



Raw Materials



Punching



Cutting



Riveting



Eyeletting



Sewing



Heat - Setting



Molding



Making up



Finished Goods



Packing



Inspection

SAFETY SHOES TEST



Toecap Test ≥ 200 Joules



Midsole Test ≥ 1200 Newtons



ESD Anti-Static Test



Tear Strength ≥ 120 N



**Bondness Test
 ≥ 4.0 N/mm**



Flex Tester $\geq 36,000$ T

Canton Fair



SAFETY SHOES



RAIN BOOTS



PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY