

Product Description

□□□□□	□□□□□□□□□□□□□□□□
□□□	SRS006
□□□□□□□	□□□□□□□□ □□□□□□□□□□□
□□□	1.□□□□□□□□□□□□□□□□200J
	2.□□□□non□
□□□	1.□□□□□□□□□□□□□□□□1100□□□□
	2.□□□□non□
□□	□□□□□□□
□□	PU□□□□
□□	□□□□□□□□□□□□□□□□
□□□	□□EVA□□□□□□□□□□HI-POLY□□PU
□□□	□□
□□□	□□□
□□□	□□36-46□□□□2-12□
□□□	CE EN ISO 20345 S1-P□□□□
□□□	6□□
□□	□□□□□□□□□□□□10□
□□□□□	58.5x40x32.5□□
□□□□□□□□	3300pairs / 1x20'□□□□ 6600pairs / 1x40'□□

Product Pictures





SAFETY SHOES TEST



Toecap Test ≥ 200 Joules



Midsole Test ≥ 1200 Newtons



ESD Anti-Static Test



Tear Strength ≥ 120 N



**Bondness Test
 ≥ 4.0 N/mm**



Flex Tester $\geq 36,000$ T

Canton Fair



SAFETY SHOES



RAIN BOOTS



PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY

