

Product Description

| | |
|----------|--|
| 00000 | 00000000000000000000 |
| 000 | SRS01H |
| 0000000 | 0000000 0000000 |
| 000 | 1.0000200000 |
| | 2.0000non0 |
| 000 | 000 |
| 00 | 000 |
| 00 | PU0000 |
| 000 | 00000000000000000000 |
| 000 | 00EVA0HI-POLY0PU0000000000000000000000 |
| 000 | 000 |
| 000 | 36-46 |
| 000 | CE EN ISO 20345 SB SRC000 |
| 000 | 00/00/000/0000000000000000 |
| 000 | 000 |
| 000 | 600 |
| 00 | 00001000001000 |
| 0000 | 59 x 44 x 3300 |
| 00000000 | 3200pairs / 1x20'00 6400pairs / 1x40'00 |

Product Pictures







SAFETY SHOES TEST



Toecap Test ≥ 200 Joules



Midsole Test ≥ 1200 Newtons



ESD Anti-Static Test



Tear Strength ≥ 120 N



**Bondness Test
 ≥ 4.0 N/mm**



Flex Tester $\geq 36,000$ T

SHOES MATERIALS



Genuine Cow Leather



CE Steel Toe cap



CE Steel Plate



Composite Toe cap



Different Eyelets



Durable Lace



Breathable Lining



Comfortable Insoles



PU or RUBBER or TPU soles

Canton Fair



SAFETY SHOES



RAIN BOOTS



PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY