

Product Description

品名	超厚超宽超软超静音超防滑超耐磨超耐用超静音超防滑超耐磨超耐用
型号	TH005L
材质	超厚超宽超软超静音超防滑超耐磨超耐用超静音超防滑超耐磨超耐用 超厚超宽超软超静音超防滑超耐磨超耐用超静音超防滑超耐磨超耐用
特点	1.超厚超宽超软超静音超防滑超耐磨超耐用超静音超防滑超耐磨超耐用 2.超厚超宽超软超静音超防滑超耐磨超耐用超静音超防滑超耐磨超耐用
规格	1.超厚超宽超软超静音超防滑超耐磨超耐用超静音超防滑超耐磨超耐用 2.超厚超宽超软超静音超防滑超耐磨超耐用超静音超防滑超耐磨超耐用
重量	1.1kg/㎡
颜色	超厚超宽超软超静音超防滑超耐磨超耐用超静音超防滑超耐磨超耐用
产地	超厚超宽超软超静音超防滑超耐磨超耐用超静音超防滑超耐磨超耐用
品牌	超厚超宽超软超静音超防滑超耐磨超耐用超静音超防滑超耐磨超耐用
包装	超厚超宽超软超静音超防滑超耐磨超耐用超静音超防滑超耐磨超耐用
保质期	超厚超宽超软超静音超防滑超耐磨超耐用超静音超防滑超耐磨超耐用
适用场所	超厚超宽超软超静音超防滑超耐磨超耐用超静音超防滑超耐磨超耐用
认证	超厚超宽超软超静音超防滑超耐磨超耐用超静音超防滑超耐磨超耐用
厚度	37-47mm/3-13mm
标准	超厚超宽超软超静音超防滑超耐磨超耐用超静音超防滑超耐磨超耐用
厚度	6mm
重量	超厚超宽超软超静音超防滑超耐磨超耐用超静音超防滑超耐磨超耐用
尺寸	58.5 x 40 x 32.5mm
包装	3300pairs / 1x20'超厚超宽超软超静音超防滑超耐磨超耐用超静音超防滑超耐磨超耐用 6600pairs / 1x40'超厚超宽超软超静音超防滑超耐磨超耐用超静音超防滑超耐磨超耐用

Product Pictures





Company Information



Intertek

EC Type Examination Certificate

CE

Issued to:	SHANGHAI HONGYUAN SHIYE CO., LTD. SHANGHAI INDUSTRIAL ZONE, JIANGNAN TOWN, NUSU 321117, ZHEJIANG PROVINCE, CHINA
Authorised Representative:	Intertek Asia SAFETY PRODUCTS APC (S) LTD. 1201 Village Square Street, Jersey Science Centre, Paragon Park, China
Date of Issue:	13 January 2018
Expiry Date:	13 February 2020
Certificate No.:	LEC170002947 (extension of certificate LEC170294719)
Product Reference(s):	Safety Plug: 480V 10A/15A 480V 10A/20A 480V 10A/25A 480V 10A/30A 50V 20A 50V 30A
Description:	Construction: Insulation Type: Plug Material: Steel Lead: 0.05 Wire: 0.05 (PVC) Mount: ACS Type Marking: See certificate No. Type Range: 05-30 Category: 05P-10A

C.M. 1687-02947

EU 1687-02947

P. H. 1687-02947

Intertek Testing Services (UK) Limited
110 Woodhouse Lane, Leamington Spa, CV32 3AH, UK
Tel: +44 (0)1922 434200
Fax: +44 (0)1922 434241
Email: certification@intertek.com



Production Process



Raw Materials



Punching



Cutting



Riveting



Eyeletting



Sewing



Heat - Setting



Molding



Making up



Finished Goods



Packing



Inspection

Canton Fair



SAFETY SHOES



RAIN BOOTS



PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY