

Product Description

□□□□	□□□□□□□□□□□□□□□□S3 SRC
□□□	TM004
□□□□□□	□□□□□□ □□□PU□□□□□□
□□□	1.□□□□□□□□200J
	2.□□□□□□□□
□□□	1.□□□□1100□□□□□□
	2.□□□□□□□□
□□	PU□□□□
□□	PU□□□□
□□□	□□□□□□□□
□□□	□□□□□□EVA□□□□□□□□
□□□	PU□□
□□□	□□□□
□□□	4-12□38-46□
□□□	S3 SRC
□□□	6□□□□□□□□□□□□□□
□□	□□□□□□□□□□10□□
□□□□	58.5x40x32.5□□
□□□□□□□□	3200pairs / 1x20'□□ 6400pairs / 1x40'□□

Product Pictures





SAFETY SHOES TEST



Toecap Test ≥ 200 Joules



Midsole Test ≥ 1200 Newtons



ESD Anti-Static Test



Tear Strength ≥ 120 N



Bondness Test ≥ 4.0 N/mm



Flex Tester $\geq 36,000$ T

Production Process



Raw Materials



Punching



Cutting



Riveting



Eyeletting



Sewing



Heat - Setting



Molding



Making up



Finished Goods



Packing



Inspection