Product Description

[illegible]	CE[illegible]
[illegible]	TM008L.
[illegible]	[illegible] [illegible]PU / PU[illegible]
[illegible]	1.[illegible]200[illegible]
	2.[illegible]
[illegible]	1.[illegible]1100[illegible]
	2.[illegible]
[illegible]	PU[illegible]
[illegible]	PU[illegible]
[illegible]	[illegible]
[illegible]	[illegible]EVA[illegible]
[illegible]	PU[illegible]
[illegible]	[illegible]
[illegible]	38-47
[illegible]	CE EN ISO 20345[illegible]2011 S3 SRC
[illegible]	[illegible]/[illegible]/[illegible]/[illegible]/[illegible]
[illegible]	6[illegible]
[illegible]	[illegible]1[illegible]10[illegible]58.5 x 40 x 32.5cm
[illegible]	3300PAIR / 1x20'[illegible] 6600PAIR / 1x40'[illegible]

Product Pictures

TIGER MASTER

Production Process

Raw Materials

Punching

Cutting

Sewing

Eyeletting

Riveting

Heat - Setting

Molding

Making up

Inspection

Packing

Finished Goods

Canton Fair

SAFETY SHOES

RAIN BOOTS

PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY

SAFETY SHOES TEST

Toecap Test≥200 Joules

Midsole Test≥1200 Newtons

ESD Anti-Static Test

Tear Strength ≥120N

Bondness Test
≥4.0N/mm

Flex Tester ≥ 36,000T