

Product Description

□□□□□	□□□□□□□□□□□□□□□□
□□□	TM009
□□□□□□□	□□□□□□ PU□□□□□□
□□□	□□□□□□200□□□□ □ASTM F2413-18 M I / 75 C / 75□CE EN ISO 20345□□□□ □□□□□□□□
□□□	□□□□1100□□□□□□□□ □ASTM F2413-18 M I / 75 C / 75□CE EN ISO 20345□□□□ □□□□□□□□
□□□	□□□□□□□□
□□	PU□□□□□□
□□	PU□□□□
□□□	□□□□□□
□□□	□□EVA□□□□□□□□□□□□
□□□	PU□□□
□□□	□□□□
□□□	□□37-47
□□□	6 □
□□□	□□/□□/□□□□/□□□□□□□□□□□□□□□□
□□	□□□□1□□□□10□□□□□□□□ 59 x 44 x 33□□
□□□□□□□□	3300pairs / 1x20'□□□□ 6600pairs / 1x40'□□□□

Product Pictures





Production Process



Raw Materials



Punching



Cutting



Riveting



Eyeletting



Sewing



Heat - Setting



Molding



Making up



Finished Goods



Packing



Inspection

SAFETY SHOES TEST



Toecap Test ≥ 200 Joules



Midsole Test ≥ 1200 Newtons



ESD Anti-Static Test



Tear Strength ≥ 120 N



**Bondness Test
 ≥ 4.0 N/mm**



Flex Tester $\geq 36,000$ T

Canton Fair



SAFETY SHOES



RAIN BOOTS



PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY