

## Product Description

□□□□□	□□□□□□□□□□□□□□
□□□	TM010
□□□□□□	□□□□□ PU□□□□□
□□□	□□□□□200□□□□ □ASTM F2413-18 M I / 75 C / 75□CE EN ISO 20345□□□□ □□□□□□□□
□□□	□□□□1100□□□□□□□□ □ASTM F2413-18 M I / 75 C / 75□CE EN ISO 20345□□□□ □□□□□□□□
□□□	D□
□□□	□□□□□□□□
□□	PU□□□□□
□□	PU□□□
□□□	□□□□□
□□□	□□EVA□□□□□□□□□□□□
□□□	PU□□□
□□□	□□□
□□□	□□38-46
□□□	6 □
□□□	□□/□□/□□□□□□□□□□□□□□□□□□□□□□□□
□□	□□□□1□□□□□10□□□□□□□□□ 59 x 44 x 33□□
□□□□□□□□	3300pairs / 1x20'□□□□ 6600pairs / 1x40'□□□

## Product Pictures





# Production Process



Raw Materials



Punching



Cutting



Riveting



Eyeletting



Sewing



Heat - Setting



Molding



Making up



Finished Goods



Packing



Inspection



# SAFETY SHOES TEST



**Toecap Test  $\geq 200$  Joules**



**Midsole Test  $\geq 1200$  Newtons**



**ESD Anti-Static Test**



**Tear Strength  $\geq 120$ N**



**Bondness Test  
 $\geq 4.0$ N/mm**



**Flex Tester  $\geq 36,000$ T**

# Canton Fair



## SAFETY SHOES



## RAIN BOOTS



PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY