

## Product Description

Model	TM055L
Material	PU/PU
Weight	1. 200g
	2. 200g
Weight	1. 1100g
	2. 1100g
Material	PU
Material	PU
Material	EVA
Material	
Material	
Material	36-47
Material	CE EN ISO 20345:2011 SB-P SRC O1 O2 O3 SB S1 S1-P S2 S3
Material	6mm
Material	
Material	
Material	10mm 58.5 x 40 x 32.5mm
Material	3300pAirs /1x20' / 6600pAirs /1x40'

## Product Pictures



200 JOULE  
TOECAP



SLIP-  
RESISTANT



SHOCK  
ABSORPTION



ANTI-STATIC



PETROL AND  
CHEMICAL  
RESISTANT



ANTI-NAIL  
MIDSOLE



OIL  
RESISTANT







# [ PRODUCTION PROCESS ]



Raw Materials



Punching



Cutting



Riveting



Eyeletting



Sewing



Heat - Setting



Molding



Making up



Finished Goods



Packing



Inspection

# SAFETY SHOES TEST



**Toecap Test  $\geq 200$  Joules**



**Midsole Test  $\geq 1200$  Newtons**



**ESD Anti-Static Test**



**Tear Strength  $\geq 120$ N**



**Bondness Test  
 $\geq 4.0$ N/mm**



**Flex Tester  $\geq 36,000$ T**



# Canton Fair



## SAFETY SHOES



## RAIN BOOTS



PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY