

Product Description

□□□□	□□□□□□□□□□□□□□□□
□□□	TM3006.
□□□□□□	□□□□□□□□ □□□□□□□□□□□□□□
□□□	□□□□□□□□200□□□ □□□□□□□□□□□□□□□□ □□□□□□
□□□	□□□□□□□□1100□□□ □□□□□□□□□□□□□□□□ □□□□□□
□□□	1.20□□/□□
□□□	□□□
□□□	PU□□□□
□□□	PU□□□□
□□□	□□□□□□
□□□	□□□EVA□□□□□□□□
□□□	□□
□□□	□□□
□□□	38-46□□
□□□	3. □□□
□□□	0.1L /□/□□/□□/□□□□□□□□□□□□□□□□
□□□	□□□□1□□□□□□□□10□□□□□□□□58.5 x 40 x 32.5 cm
□□□□□□□□	3300PAIR / 1x20'□□ 6600PAIR / 1x40'□□

Product Pictures





SAFETY SHOES TEST



Toecap Test ≥ 200 Joules



Midsole Test ≥ 1200 Newtons



ESD Anti-Static Test



Tear Strength ≥ 120 N



**Bondness Test
 ≥ 4.0 N/mm**



Flex Tester $\geq 36,000$ T

Canton Fair



SAFETY SHOES



RAIN BOOTS



PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY

Production Process



Raw Materials



Punching



Cutting



Riveting



Eyeletting



Sewing



Heat - Setting



Molding



Making up



Finished Goods



Packing



Inspection