Product Description

	TM3022
000000	00000 00 0 00 000PU/ PU 0 00
000	1.0 00 000200 00000000000000000000
	2.00000 0
	1. 0 0000 1100 000 0000000000000000
	2.00000 0
	000 00 EVA 00 00 00 000 000 000 00 00 00 00 & 00 0 000
	PU□□
	38-47
	CE EN ISO 20345:2011 S1-P SRC [] [][[]
000	
	1 pairs per c 0000000 10 00
0000	59 x 44 x 33 cm
	3200 /1x20"

Product Pictures







SLIP- SHOCK ABSORPTION







ANTI-STATIC PETROL AND CHEMICAL RESISTANT



ANTI-NAIL MIDSOLE



OIL RESISTANT







COMPANY INFORMATION

TIGER MASTER







TIGER MASTER OFFICE SHOW





TIGER MASTER SAMPLE ROOM





SAFETY SHOES TEST





Toecap Test≥200 Joules



Midsole Test≥1200 Newtons



ESD Anti-Static Test



Tear Strength ≥120N



Bondness Test ≥4.0N/mm



Flex Tester ≥ 36,000T

Production Process



Canton Fair





SAFETY SHOES



RAIN BOOTS





PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY

PERSONAL PROTECTIVE EQUIPMENT WORK SAFETY SOLUTION PROVIDER























