

## Product Description

□□□□	□□□□□□□□□□
□□□	TM112
□□□□□	□□□□□□□□ □□□□□□□□□□□□□□
□□□	□□□□□□□□□□□□□□□□200□□□□ □ASTM F2413-18 M I/75 C/75□CE EN ISO 20345□□□□ □□□□□□□□
□□□	□□□□□□□□□□□□□□□□□□1100□□□□ □ASTM F2413-18 M I/75 C/75□CE EN ISO 20345□□□□ □□□□□□□□
□□□	1.20□□/□□
□□□	□□□
□□□	PU□□□□
□□□	PU□□□□
□□□	□□□□□□□□□□□□□□
Sockliner□	□□□□□□□□□□□□□□□□EVA
□□□	PU□□
□□□	□□
□□□	□□38-46
□□□	6 □□
□□□	oIL/□/□□/□□/□□□□□□□□□□□□□□□□□□□□□□□□
□□□	□□□□□□1□□□□□□10□□□□□□□□□□59 x 44 x 33□□
□□□□□□□□□□	3200pAirs /1x20'□□ 6400pAirs /1x40'□□

## Product Pictures





# SAFETY SHOES TEST



**Toecap Test  $\geq 200$  Joules**



**Midsole Test  $\geq 1200$  Newtons**



**ESD Anti-Static Test**



**Tear Strength  $\geq 120$ N**



**Bondness Test  
 $\geq 4.0$ N/mm**



**Flex Tester  $\geq 36,000$ T**



# Canton Fair



## SAFETY SHOES



## RAIN BOOTS



PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY

# Production Process



Raw Materials



Punching



Cutting



Riveting



Eyeletting



Sewing



Heat - Setting



Molding



Making up



Finished Goods



Packing



Inspection