

Product Description

Produktname:	Tiger Master Brand Leder Konstruktion Sicherheitsstiefel Stahlkappe
Artikelnummer:	DTA032H
Obermaterial und Sohle:	Obermaterial: Glattes Rindspaltleder Sohle: PU Dual Density
Zehe:	1. Stahlkappe, es kann stoßfest 200 Joule sein. 2. nicht ist auch vorgesehen.
Zwischensohle:	1. Stahlplatte, es kann sein Puktion beständig 1100 Newton. 2. Nicht ist ebenfalls unter der Voraussetzung
Gewicht:	1,2 kg / Pr
Halsband:	High Density Oxford Stoff mit Schwamm
Zunge:	Oxford-Gewebe mit hoher Dichte
Futter:	Black Air & Dry Sandwich-Mesh-Gewebe (Ihre Füße bleiben trocken und komfortabel)
Sockliner:	Geformtes EVA oder HI-POLY oder PU (Reduzieren Sie die Schmerzen und Müdigkeit bei der täglichen Arbeit erheblich)
Konstruktion:	PU-Injektion
Höhe:	Hoher Knöchel
Größe:	37-47 (3-13)
Standard:	CE EN ISO 20345 S1P SRC oder andere als Ihre Anforderungen
Garantie:	6 Monate
Paket:	1 Paar pro cOlor innere Kastenverpackung, 10 Paare pro Karton.
Kartongröße	59 x 44 x 33 cm
Lademege des Containers:	3200pairs / 1x20 'Behälter 6400pairs / 1x40 'container

Product Pictures





Company Information



Intertek

EC Type Examination Certificate

CE

Issued to:	SHANGHAI HONGSHAN SHIBAO CO., LTD. SHANGHAI INDUSTRIAL ZONE, JIANGNAN TOWN, NUSUN 2017, JIANGSU PROVINCE, CHINA																		
Authorised Representative:	Intertek Asia SAFETY PRODUCTS APC (S) LTD. 1201 Village Square Street, Avenue 6, Singapore, Singapore Singapore 549511, Singapore																		
Date of Issue:	11 January 2018																		
Expiry Date:	11 January 2020																		
Certificate No.:	LEC170002947 (extension of certificate LEC160341196)																		
Product Reference(s):	Safety Plug: 48501-08002 48500-08004 48501-08004 48501-08009 800-081-081-081																		
Description:	<table border="0"> <tr> <td>Construction:</td> <td>Insulation</td> </tr> <tr> <td>Terminal:</td> <td>Open contact</td> </tr> <tr> <td>Material:</td> <td>Open plug</td> </tr> <tr> <td>Color:</td> <td>White</td> </tr> <tr> <td>Line:</td> <td>800 (Purple)</td> </tr> <tr> <td>Mount:</td> <td>ACB</td> </tr> <tr> <td>Test frequency:</td> <td>See technical file</td> </tr> <tr> <td>Test range:</td> <td>0.4A</td> </tr> <tr> <td>Category:</td> <td>081-081</td> </tr> </table>	Construction:	Insulation	Terminal:	Open contact	Material:	Open plug	Color:	White	Line:	800 (Purple)	Mount:	ACB	Test frequency:	See technical file	Test range:	0.4A	Category:	081-081
Construction:	Insulation																		
Terminal:	Open contact																		
Material:	Open plug																		
Color:	White																		
Line:	800 (Purple)																		
Mount:	ACB																		
Test frequency:	See technical file																		
Test range:	0.4A																		
Category:	081-081																		

C.M.

 **Product Reference:** LEC170002947 (extension of certificate LEC160341196)

Issue Date: 11/01/2018

Valid Until: 11/01/2020

Product Reference: LEC170002947 (extension of certificate LEC160341196)



Production Process



Raw Materials



Punching



Cutting



Riveting



Eyeletting



Sewing



Heat - Setting



Molding



Making up



Finished Goods



Packing



Inspection

SAFETY SHOES TEST



Toecap Test ≥ 200 Joules



Midsole Test ≥ 1200 Newtons



ESD Anti-Static Test



Tear Strength ≥ 120 N



Bondness Test ≥ 4.0 N/mm



Flex Tester $\geq 36,000$ T

Canton Fair



SAFETY SHOES



RAIN BOOTS



PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY