

Product Description

Nombre del producto:	Botas de seguridad soldadas Goodyear de cuero de plena flor marrón con puntera de acero
Artículo No:	GY017
Parte superior y suela:	Parte superior: cuero de plena flor marrón Suela: goma (sin olor penetrante), resistente a la abrasión, al aceite y al deslizamiento.
Dedo del pie:	1. Puntera de acero, puede ser resistente a los impactos de 200 julios. 2. non también se proporciona.
Entresuela:	1) Acero placa, puede ser punción resistente 1100 Newton. 2) No es además previsto
Peso:	1,4 kilogramos / pr
Collar:	Cuero artificial PU con esponja
Lengua:	Cuero suave de grano completo
Revestimiento:	Tela cambrella marrón u otras (sus pies se mantendrán cómodos)
Plantilla:	HI-POLY moldeado u otros (reduce en gran medida el dolor y la fatiga de los pies del trabajo diario)
Construcción:	Goodyear welted
Altura:	6 pulgadas
Tamaño:	37-47 (3-13)
Estándar:	CE EN ISO 20345 S1P SRC u otros como sus requisitos
Garantizar:	6 meses
Paquete:	Embalaje de caja interior de color, 10 pares en una caja de cartón.
Tamaño del cartón	59 x 53 x 33 cm
Cantidad de carga del contenedor:	2600 pares / 1x20 'contenedor 5200 pares / contenedor 1x40 '

Product Pictures





Company Information



Intertek

EC Type Examination Certificate

CE	Issued to: FUJIAN HONGJIAN SHISEI CO., LTD. SHANGHAI INDUSTRIAL ZONE, JIANGNAN TOWN, NUSU 3211, ZHONGSHAN PROVINCE, CHINA																		
Authorised Representative:	Intertek Asia SAFETY PRODUCTS APC (S) LTD. 1201 Village Square Street, Village Square Mall, Singapore 138901, CHINA																		
Date of Issue:	11 January 2018																		
Expiry Date:	11 February 2020																		
Certificate No.:	LEC170002947 (extension of certificate LEC170294796)																		
Product Reference(s):	Safety Group: 48801-48802 48803-48804 48805-48806 48807-48808 890-891-892-893																		
Description:	<table border="0"> <tr> <td>Construction:</td> <td>Insulation</td> </tr> <tr> <td>Turning:</td> <td>Open ended</td> </tr> <tr> <td>Material:</td> <td>Steel plate</td> </tr> <tr> <td>Color:</td> <td>Black</td> </tr> <tr> <td>Size:</td> <td>800 (Length)</td> </tr> <tr> <td>Mount:</td> <td>ACB</td> </tr> <tr> <td>Test frequency:</td> <td>See technical file</td> </tr> <tr> <td>Test range:</td> <td>30-45</td> </tr> <tr> <td>Category:</td> <td>890-893</td> </tr> </table>	Construction:	Insulation	Turning:	Open ended	Material:	Steel plate	Color:	Black	Size:	800 (Length)	Mount:	ACB	Test frequency:	See technical file	Test range:	30-45	Category:	890-893
Construction:	Insulation																		
Turning:	Open ended																		
Material:	Steel plate																		
Color:	Black																		
Size:	800 (Length)																		
Mount:	ACB																		
Test frequency:	See technical file																		
Test range:	30-45																		
Category:	890-893																		
Authorized Representative:	<i>C.M.</i> 1687-0218																		
Intertek Representative:	<i>[Signature]</i> 1687-0218																		
Product Reference:	1687-0218																		
Product Name:	1687-0218																		
Product Description:	1687-0218																		
Product Category:	1687-0218																		
Product Code:	1687-0218																		
Product Model:	1687-0218																		
Product Type:	1687-0218																		
Product Material:	1687-0218																		
Product Color:	1687-0218																		
Product Size:	1687-0218																		
Product Mount:	1687-0218																		
Product Test Frequency:	1687-0218																		
Product Test Range:	1687-0218																		
Product Category:	1687-0218																		



Production Process



Raw Materials



Punching



Cutting



Riveting



Eyeletting



Sewing



Heat - Setting



Molding



Making up



Finished Goods



Packing



Inspection

Canton Fair



SAFETY SHOES



RAIN BOOTS



PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY