

Product Description

Nombre del producto:	Las botas de seguridad con punta de acero de la PU de cuero genuino aprobado por la CE funcionan
Artículo No:	SJ0196
Parte superior y suela:	Parte superior: cuero genuino marrón Suela: PU de doble densidad.
Dedo del pie:	1. Puntera de acero, puede ser resistente a los impactos de 200 julios. 2. non también se proporciona.
Entresuela:	1) Placa de acero, puede ser punción resistente 1100 Newton. 2) No es además previsto
Peso:	1,2 kilogramos / pr
Collar:	Tela oxford de alta densidad con esponja
Lengua:	Tejido oxford de alta densidad, resistente a la arena.
Revestimiento:	Aire marrón y tela de malla seca (sus pies se mantendrán cómodos)
Plantillas:	HI-POLY o PU moldeados (reducen enormemente el dolor y la fatiga del trabajo diario)
Construcción:	Inyección de PU
Altura:	Tobillo alto
Tamaño:	37-47 (3-13)
Estándar:	CE EN ISO 20345 S1P SRC u otros como sus requisitos
Garantizar:	6 meses
Paquete:	Embalaje de caja interior de color, 10 pares en una caja de cartón.
Tamaño del cartón	59 x 44 x 33 cm
Cantidad de carga del contenedor:	3200 pares / 1x20 'contenedor 6400 pares / contenedor 1x40 '

Product Pictures





Company Information



Intertek

EC Type Examination Certificate

CE

Issued to:	RUANG HONGKUN 59082-02, LTD. SUNGU INDUSTRIAL ZONE, JINCHANG TOWN, NANYANG CITY, ZHANGJIANG PROVINCE, CHINA																		
Authorised Representative:	Intertek Asia SAFETY PRODUCTS APC (S) LTD. 1501 Village Square Street, Anson Road, Singapore 069769, Singapore																		
Date of Issue:	13 January 2018																		
Expiry Date:	13 February 2020																		
Certificate No.:	LEC170002947 (Extension of certificate LEC170294719)																		
Product Reference(s):	Safety Plug 480V 2P/3P 480V 2P/3P 480V 2P/3P 480V 2P/3P 500 2P/3P 50A																		
Description:	<table border="0"> <tr> <td>Construction:</td> <td>Insulation</td> </tr> <tr> <td>Terminal:</td> <td>Open contact</td> </tr> <tr> <td>Material:</td> <td>Open wire</td> </tr> <tr> <td>Lead:</td> <td>5000</td> </tr> <tr> <td>Wire:</td> <td>5000 (PVC)</td> </tr> <tr> <td>Mount:</td> <td>ACB</td> </tr> <tr> <td>Test frequency:</td> <td>See standard file</td> </tr> <tr> <td>Test range:</td> <td>20-40</td> </tr> <tr> <td>Category:</td> <td>500 2P/3P</td> </tr> </table>	Construction:	Insulation	Terminal:	Open contact	Material:	Open wire	Lead:	5000	Wire:	5000 (PVC)	Mount:	ACB	Test frequency:	See standard file	Test range:	20-40	Category:	500 2P/3P
Construction:	Insulation																		
Terminal:	Open contact																		
Material:	Open wire																		
Lead:	5000																		
Wire:	5000 (PVC)																		
Mount:	ACB																		
Test frequency:	See standard file																		
Test range:	20-40																		
Category:	500 2P/3P																		

EU Declaration of Conformity:
I, the undersigned, being the authorised representative of the manufacturer, declare that the product covered by this certificate is in conformity with the applicable harmonised standards referred to in the certificate, and that the product is therefore suitable for the use intended by the manufacturer.

Signature: *C.M.* 15/01/2018

Product Name: Safety Plug 15/01/2018

Authorised Representative: Intertek Asia SAFETY PRODUCTS APC (S) LTD.
1501 Village Square Street, Anson Road, Singapore 069769, Singapore

EU Declaration of Conformity:
I, the undersigned, being the authorised representative of the manufacturer, declare that the product covered by this certificate is in conformity with the applicable harmonised standards referred to in the certificate, and that the product is therefore suitable for the use intended by the manufacturer.



Production Process



Raw Materials



Punching



Cutting



Riveting



Eyeletting



Sewing



Heat - Setting



Molding



Making up



Finished Goods



Packing



Inspection

Canton Fair



SAFETY SHOES



RAIN BOOTS



PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY