

Product Description

Nom du produit:	8 pouces antidérapant Tiger Master Brand Bottes de sécurité en cuir à embout d'acier Hommes
Numéro d'article:	SD5065
Tige et semelle:	Tige: cuir de vache refendu gaufré Semelle: PU double densité
Doigt de pied:	1. Embout en acier, il peut être résistant aux chocs 200 Joules. 2. non est également fourni.
Semelle intermédiaire:	1. Plaque d'acier, ça peut être crevaillon résistant 1100 newton. 2. Non est aussi à condition de
Poids:	1,2 kg / pr
Collier:	Cuir artificiel PU avec éponge
Langue:	Cuir artificiel PU, résistant au sable
Doublure:	Tissu mesh Air & Dry (vos pieds resteront au sec et confortables)
Semelle intérieure:	EVA moulé ou autres (réduisez considérablement votre douleur et votre fatigue du travail quotidien)
Construction:	Injection PU
La taille:	8 pouces
Taille:	37-47 (3-13)
La norme:	CE EN ISO 20345 SBP SRC ou autres selon vos besoins
Garantie:	6 mois
Paquet:	1 paire par cemballage intérieur de boîte d'olor, 10 paires par carton.
Taille du carton	59 x 44 x 33 cm
Charger la quantité de conteneur:	3000 paires / 1x20 'conteneur Conteneur de 6000 paires / 1x40 '

Product Pictures





Company Information



Intertek

EC Type Examination Certificate



Issued to: FUJIAN HONGJIAN SHISEI CO., LTD.
SHANGHAI INDUSTRIAL ZONE, JIANGNAN TOWN, NINGBO
321117, ZHEJIANG PROVINCE, CHINA

Authorised Representative: HANDEHU NEW SAFETY PRODUCTS APLC (S) LTD.
1201 Village, North Zone, Jiangyin District, Suzhou,
Henan Province, China

Date of Issue: 11 January 2018

Expiry Date: 11 February 2020

Certificate No.: L20170002947 (extension of certificate L20170294719)

Product Reference(s): Safety Valve
48201-08010
48200-08024
48201-08018
48201-08019
800 200 300 400

Description:

Construction:	Iron/Steel
Working Pressure:	20bar-16bar
Material:	304
Port:	DN25
Size:	1000 (Supply)
Mount:	AC30
Test Standard:	EN 10228-1/2
Test Range:	20-16
Category:	001-010

Authorised Representative: *C.M.* 168102918

Product Reference: *C.M.* 168102918

Issued by: Intertek (UK) Limited
111, Market Street, Lymington, Hampshire, SO41 1DL, United Kingdom



Production Process



Raw Materials



Punching



Cutting



Riveting



Eyeletting



Sewing



Heat - Setting



Molding



Making up



Finished Goods



Packing



Inspection

SAFETY SHOES TEST



Toecap Test ≥ 200 Joules



Midsole Test ≥ 1200 Newtons



ESD Anti-Static Test



Tear Strength ≥ 120 N



**Bondness Test
 ≥ 4.0 N/mm**



Flex Tester $\geq 36,000$ T

Canton Fair



SAFETY SHOES



RAIN BOOTS



PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY