

Product Description

Nom du produit:	Bottes S3 SRC High Rigger
Numéro d'article:	Tm5009
Upper et Sole:	Tige: cuir de vachette divisé en relief Semelle: semelle à double densité PU / PU
Doigt de pied:	1. Casquette en acier pour avoir une résistance à l'impact de 200 joules. 2. Toe non en acier est également fourni.
Intermédiaire:	1. Plaque d'acier à ponction résistante à la ponction 1100 Newton. 2. La plaque non acier est également fournie
Collier et langue:	Sans collier
style:	Pas de bottes de soudage en dentelle
Garniture:	Tissu de maille d'air (il sera gardé vos pieds confortables)
SOCKLINER:	Eva moulée anti-statique recouverte de tissu de maille d'air ou d'autres comme vos exigences (réduisez considérablement la douleur et la fatigue des pieds du travail quotidien)
Construction:	Injection de PU
Hauteur:	29-30 cm
Taille:	38-47
Standard:	CE EN ISO 20345: 2011 S3P SRC
Garantie:	6 mois
Paquet:	Couleur Inner Box Emballage, 10 paires dans un carton.
Taille de carton	68 x 65 x 34.5 cm
Charge Quantité de conteneur:	1800Paires / 1x20 'Conteneur Conteneur 3600Paires / 1x40 '

Product Pictures





Production Process



Raw Materials



Punching



Cutting



Riveting



Eyeletting



Sewing



Heat - Setting



Molding



Making up



Finished Goods



Packing



Inspection

Canton Fair



SAFETY SHOES



RAIN BOOTS



PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY

SAFETY SHOES TEST



Toecap Test ≥ 200 Joules



Midsole Test ≥ 1200 Newtons



ESD Anti-Static Test



Tear Strength ≥ 120 N



**Bondness Test
 ≥ 4.0 N/mm**



Flex Tester $\geq 36,000$ T