

Product Description

Product Name:	Anti slip oil acid resistant anti puncture PVC safety rain boots steel toe
Item No:	109
Color:	Black upper with black sole
Size:	EUR 38-47
Height:	35 cm (Average)
Average weight	2.2-2.3 kgs per pair
Material	100% pure PVC material (easy to wash)
Lining:	Polyester (easily dried fabric)
Construction	PVC injection
Standard	Meet CE standard
Characteristics	<ol style="list-style-type: none">1. Water / Acid / Alkali / oil / grease resistant, non-slip, anti-static pvc boots.2. outsole is abrasion resistant and Contract.3. Ankle protection, energy absorption on the heel seat region, strengthening toe and heel.4. Steel toe cap to be impact resistant 200 joules.5. Steel mid plate to be puncture resistant 1100 newtons.
Guarantee:	5 months, robust and solid quality.
Package:	1 pair per poly bag, 10 pairs per carton. or as your requirements.
G.W./N.W.:	26 kgs/ 24 kgs
Delivery time:	About 40 days after receiving the deposit.

Product Pictures



200 JOULE
TOECAP



SLIP-
RESISTANT



SHOCK
ABSORPTION



ANTI-STATIC



PETROL AND
CHEMICAL
RESISTANT



ANTI-NAIL
MIDSOLE



OIL
RESISTANT





Company Information



Automatic Injection Molding Machine



Puncture Testing Machine



Impact Resistant Testing Machine



Tensile testing machine

Deburring



Production Process



1. Mixing Materials



2. Putting Polyester Lining



3. PVC Injection



4. Open The Mould



5. Demoulding



6. Tidying



7. Printing



8. Inspection



9. Packaging

Canton Fair



SAFETY SHOES



RAIN BOOTS



PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY

PERSONAL PROTECTIVE EQUIPMENT WORK SAFETY SOLUTION PROVIDER



Safety Work Shoes

[View More](#)



PVC Rain Boots

[View More](#)



Military Army Boots

[View More](#)



Rain Coat/ Suit

[View More](#)



Work Garments

[View More](#)



Reflective Safety Vest

[View More](#)



Safety Work Gloves

[View More](#)



Safety Helmets

[View More](#)



Safety Harness

[View More](#)



[View More](#)



Traffic Cone

[View More](#)



Warning Tape

[View Details](#)