

## Product Description

Product Name:	CE approved lightweight fiberglass toe puncture proof safety shoes
Item No:	BTA049
Upper and Sole:	Split nubuck leather upper, PU/ PU dual density sole,
Toe cap:	Fiberglass toe to be impact resistant 200 joules. (ASTM F2413-18 M I/75 C/75, CE EN ISO 20345 standard) Non is also provided.
Mid sole:	Non-metallic anti-penetration mid sole to be puncture resistant 1100 newton. (ASTM F2413-18 M I/75 C/75, CE EN ISO 20345 standard) Non is also provided.
Certification:	CE
Style:	Laced up
Collar:	Suede leather
Tongue:	Suede leather
Lining:	Breathable air mesh fabric
Sockliner:	Moulded EVA or HI-POLY or PU
Construction:	PU injection
Size:	EUR 37-47
Guarantee:	6 months
Usage:	airport, workshop, warehouse, indoor working, general working etc.
Function:	Metal free, slip/ oil/ impact/ puncture resistant, anti static, shock absorption
Package:	1 pair per color box, 10 pairs per carton. Carton size is 58.5 x 40 x 32.5 cm
Load quantity of Container:	3200pairs /1x20' container 6400pairs /1x40' container

## Product Pictures





# Production Process



Raw Materials



Punching



Cutting



Riveting



Eyeletting



Sewing



Heat - Setting



Molding



Making up



Finished Goods



Packing



Inspection

# SAFETY SHOES TEST



**Toecap Test  $\geq 200$  Joules**



**Midsole Test  $\geq 1200$  Newtons**



**ESD Anti-Static Test**



**Tear Strength  $\geq 120$ N**



**Bondness Test  
 $\geq 4.0$ N/mm**



**Flex Tester  $\geq 36,000$ T**

# Canton Fair



## SAFETY SHOES



## RAIN BOOTS



PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY