

Product Description

Product Name:	Pink oil slip resistant steel toe puncture proof women safety shoes sports
Item No:	DTA017
Upper and Sole:	Upper: Air breathable 3D flying knitted fabric Sole: PU/ PU dual density sole
Toe:	1. Steel toe cap to be impact resistant 200 Joules. To protect your feet toe without hazard. 2. non-steel toe is also provided.
Midsole :	1. Steel plate to be puncture resistant 1100 Newton. To protect your feet without puncture by nail or sharp objects 2. non- steel plate is also provided
Collar:	3D flying knitted fabric
Tongue:	High density fabric
Lining:	Soft air sandwich mesh fabric (it will be kept your feet comfortable)
Sockliner:	Anti static Moulded EVA coated with air mesh fabric or others as your requirements (Greatly reduce your feet pain & fatigue from daily work)
Construction:	PU injection
Height:	Low ankle
Size:	38-47
Standard:	CE EN ISO 20345:2011 S1-P SRC or others.
Guarantee:	6 months
Package:	1 pairs per color inner box packing, 10 pairs in a carton.
Carton Size	58.5 x 40 x 32.5 cm
Load quantity of Container:	3300pairs /1x20' container 6600pairs /1x40' container

Product Pictures





EU TYPE EXAMINATION CERTIFICATE intertek

CE **APPROVED BODY** **RENEWING BARRI, LTD.**
 BUKUJI PLAZA FLAIA, NO.201 (SIAMBAK ROAD), FAMBIL, CEMBU
 Issue Date: 10 September 2020
 Expiry Date: 10 September 2024
 Certificate No.: 111100481 (1) (Extension by Certificate LECT94311003)
 Product Reference(s): 87420 (pvc-3324)
 87420 (pvc-2020-02)
 Description: Type of boot: High-top
 Material: Composite Toe-cap
 Sole: PU (1.5MM) / EVA (0.4MM) / PU (1.5MM) / EVA (0.4MM)
 Upper: PU (1.5MM) / EVA (0.4MM)
 Insole: EVA (0.4MM)
 Outsole: PU (1.5MM) / EVA (0.4MM)
 Heel: EVA (0.4MM)
 Toe Cap: PU (1.5MM) / EVA (0.4MM)
 Lining: EVA (0.4MM)
 Laces: PU (1.5MM) / EVA (0.4MM)

APPROVED BODY **RENEWING BARRI, LTD.**
 BUKUJI PLAZA FLAIA, NO.201 (SIAMBAK ROAD), FAMBIL, CEMBU
 Issue Date: 10 September 2020
 Expiry Date: 10 September 2024
 Certificate No.: 111100481 (1) (Extension by Certificate LECT94311003)
 Product Reference(s): 87420 (pvc-3324)
 87420 (pvc-2020-02)
 Description: Type of boot: High-top
 Material: Composite Toe-cap
 Sole: PU (1.5MM) / EVA (0.4MM) / PU (1.5MM) / EVA (0.4MM)
 Upper: PU (1.5MM) / EVA (0.4MM)
 Insole: EVA (0.4MM)
 Outsole: PU (1.5MM) / EVA (0.4MM)
 Heel: EVA (0.4MM)
 Toe Cap: PU (1.5MM) / EVA (0.4MM)
 Lining: EVA (0.4MM)
 Laces: PU (1.5MM) / EVA (0.4MM)

APPROVED BODY **RENEWING BARRI, LTD.**
 BUKUJI PLAZA FLAIA, NO.201 (SIAMBAK ROAD), FAMBIL, CEMBU
 Issue Date: 10 September 2020
 Expiry Date: 10 September 2024
 Certificate No.: 111100481 (1) (Extension by Certificate LECT94311003)
 Product Reference(s): 87420 (pvc-3324)
 87420 (pvc-2020-02)
 Description: Type of boot: High-top
 Material: Composite Toe-cap
 Sole: PU (1.5MM) / EVA (0.4MM) / PU (1.5MM) / EVA (0.4MM)
 Upper: PU (1.5MM) / EVA (0.4MM)
 Insole: EVA (0.4MM)
 Outsole: PU (1.5MM) / EVA (0.4MM)
 Heel: EVA (0.4MM)
 Toe Cap: PU (1.5MM) / EVA (0.4MM)
 Lining: EVA (0.4MM)
 Laces: PU (1.5MM) / EVA (0.4MM)

EWG

Certificate of Quality Management System

Certified that
Harbin Ana Safety Products Mfg. Co., Ltd.
 Registered Address: No.16, 11, 10th E. Building 11th, Easton Street, Highgate District, Harbin City, Heilongjiang Province
 Production Address: Lishi Village, Nongda Town, Achang District, Harbin City, Heilongjiang Province
 Office Address: 302 Jiahua Building, No.201 Changjiang Road, Nangang District, Harbin City
 Contact Email: ana@ana.com.cn
 Contact Tel: +86 451 83611111

Has established a Quality Management System which is in accordance with the Requirements of the Standard:
GB/T 19001-2016/ISO 9001:2015

SCOPE OF CERTIFICATION:
 Manufacture and Sales of Polyvinyl Chloride (PVC)
 Protective Rain Boots (Except for Production License Products)

Expiry of Certificate for Last Cycle: Mar. 8, 2024
 Validity of Certificate: May 7, 2020 to Mar. 8, 2024
 Expiry Date of the Certificate: May 7, 2024

The effectiveness of this Certificate shall be subject to periodic surveillance audits of EWG for maintenance. Conditions of surveillance of compliance can be found on <http://www.intertek.com> and <http://www.iso.org>.
 Distribution: Administration of Quality Management of Harbin Ana Safety Products Mfg. Co., Ltd.
 Expiry of this Certificate: Mar. 8, 2024
 Serial No.: V3101010

EWG *Signature*

ANAB **IAF** **UKAS**

Intertek Testing Services (UK) Limited

EU TYPE EXAMINATION CERTIFICATE intertek

CE **APPROVED BODY** **HARBIN ANA SAFETY PRODUCTS MFG. CO., LTD.**
 LISHI VILLAGE, NONGDA TOWN, ACHANG DISTRICT, HARBIN, HEILONGJIANG PROVINCE, CHINA
 Issue Date: 10 September 2020
 Expiry Date: 10 September 2024
 Certificate No.: 111100481 (1)
 Product Reference(s): 87420 (PVC)
 87420 (PVC)
 Description: Construction: PU (1.5MM) / EVA (0.4MM) / PU (1.5MM) / EVA (0.4MM)
 Material: PU (1.5MM) / EVA (0.4MM)
 Sole: PU (1.5MM) / EVA (0.4MM)
 Upper: PU (1.5MM) / EVA (0.4MM)
 Insole: EVA (0.4MM)
 Outsole: PU (1.5MM) / EVA (0.4MM)
 Heel: EVA (0.4MM)
 Toe Cap: PU (1.5MM) / EVA (0.4MM)
 Lining: EVA (0.4MM)
 Laces: PU (1.5MM) / EVA (0.4MM)

APPROVED BODY **HARBIN ANA SAFETY PRODUCTS MFG. CO., LTD.**
 LISHI VILLAGE, NONGDA TOWN, ACHANG DISTRICT, HARBIN, HEILONGJIANG PROVINCE, CHINA
 Issue Date: 10 September 2020
 Expiry Date: 10 September 2024
 Certificate No.: 111100481 (1)
 Product Reference(s): 87420 (PVC)
 87420 (PVC)
 Description: Construction: PU (1.5MM) / EVA (0.4MM)
 Material: PU (1.5MM) / EVA (0.4MM)
 Sole: PU (1.5MM) / EVA (0.4MM)
 Upper: PU (1.5MM) / EVA (0.4MM)
 Insole: EVA (0.4MM)
 Outsole: PU (1.5MM) / EVA (0.4MM)
 Heel: EVA (0.4MM)
 Toe Cap: PU (1.5MM) / EVA (0.4MM)
 Lining: EVA (0.4MM)
 Laces: PU (1.5MM) / EVA (0.4MM)

APPROVED BODY **HARBIN ANA SAFETY PRODUCTS MFG. CO., LTD.**
 LISHI VILLAGE, NONGDA TOWN, ACHANG DISTRICT, HARBIN, HEILONGJIANG PROVINCE, CHINA
 Issue Date: 10 September 2020
 Expiry Date: 10 September 2024
 Certificate No.: 111100481 (1)
 Product Reference(s): 87420 (PVC)
 87420 (PVC)
 Description: Construction: PU (1.5MM) / EVA (0.4MM)
 Material: PU (1.5MM) / EVA (0.4MM)
 Sole: PU (1.5MM) / EVA (0.4MM)
 Upper: PU (1.5MM) / EVA (0.4MM)
 Insole: EVA (0.4MM)
 Outsole: PU (1.5MM) / EVA (0.4MM)
 Heel: EVA (0.4MM)
 Toe Cap: PU (1.5MM) / EVA (0.4MM)
 Lining: EVA (0.4MM)
 Laces: PU (1.5MM) / EVA (0.4MM)

[PRODUCTION PROCESS]



Raw Materials



Punching



Cutting



Riveting



Eyeletting



Sewing



Heat - Setting



Molding



Making up



Finished Goods



Packing



Inspection

SAFETY SHOES TEST



Toecap Test ≥ 200 Joules



Midsole Test ≥ 1200 Newtons



ESD Anti-Static Test



Tear Strength ≥ 120 N



Bondness Test ≥ 4.0 N/mm



Flex Tester $\geq 36,000$ T

Canton Fair



SAFETY SHOES



RAIN BOOTS



PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY