Product Description

Product Name:	Tiger master composite toe puncture proof oil field safety shoes
Item No:	TM120
Upper and Sole:	Nubuck leather upper, PU & RUBBER sole
Toe:	1. Composite toe cap or steel toe cap to be impact resistant. To protect your feet toe without hazard.
	2. non is also provided.
Midsole :	1. Non-metallic anti-penetration insoles or steel plate to be puncture resistant. To protect your feet without puncture by nail or sharp objects.
	2. non is also provided
Collar:	High density oxford fabric
Tongue:	High density oxford fabric & nubuck leather
Lining:	Air sandwich mesh fabric lining for a comfort fit
Shoe pads:	Removable HI-POLY insole offers superior underfoot support and cushioned comfort.
Construction:	Injection moulded
Height:	Mid cut
Size:	37-47
Standard:	CE EN ISO 20345:2011 SB-P SRC or others.
Guarantee:	6 months The sole is not broken from the middle or pulled off within six month after the goods getting to destination port. No guarantee for the upper.
Function:	Heat resistant the degree of 300, oil/ acid/ petrol/ chemical/ slip/ impact/ puncture resistant, metal free, shock absorption.
Package:	1 pair per color box, 10 pairs per carton. Carton size: 59 x 44 x 33 cm
Load quantity of Container:	3200pairs /1x20' container 6400pairs /1x40' container

Product Pictures







Company Information

Tiger Master is safety shoes and PVC rain boots manufacturer. We have been qualified ISO 9001:2015 quality management system. Also, some of our hot sale models have qualified CE ENISO 20345:2011 and ASTM F2413-18. Meanwhile, we are also a professional brand for **PPE** (Personal protective equipment), especially in the fields of safety gloves, working garments, helmets, safety vest, ear muff/plug, safety harness, rain coat/suit etc.

Thank you for your interest of Tiger Master, hope you can find the products you want and start our business cooperation. If you need more information, please do not hesitate to contact us, we are always ready here.



TIGER MASTER OFFICE SHOW



TIGER MASTER SAMPLE ROOM



<section-header>

Flex Tester ≥ 36,000T

Bondness Test

≥4.0N/mm

Tear Strength ≥120N



Personal Protective Equipment Work safety solution provider

