

Product Description

Product Name:	Cemented construction oil field labor protection safety shoes to work
Item No:	TM3005
Upper and Sole:	Upper is Embossed split cow leather Sole is natural rubber, there is no bad smell
Toe cap:	Steel toe cap to be impact resistant 200 joules. (ASTM F2413-18 M I/75 C/75, CE EN ISO 20345 standard) Non is also provided.
Mid sole:	Steel plate to be puncture resistant 1100 newton. (ASTM F2413-18 M I/75 C/75, CE EN ISO 20345 standard) Non is also provided.
Weight:	1.30 kgs/ pr
Color:	Black
Collar:	PU artificial leather
Tongue:	PU artificial leather
Lining:	Soft air mesh fabric
Sockliner:	Anti static moulded EVA coated with mesh fabric
Construction:	Cemented
Height:	Middle cut
Size:	EUR 38-46
Guarantee:	3 months
Function:	Oil/ acid/ impact/ puncture/ abrasion resistant, shock absorption, Water resistant & anti static available.
Package:	1 pair per color box, 10 pairs per carton. Carton size is 59 x 44 x 33 cm
Load quantity of Container:	3200pairs /1x20' container 6400pairs /1x40' container

Product Pictures





SAFETY SHOES TEST



Toecap Test ≥ 200 Joules



Midsole Test ≥ 1200 Newtons



ESD Anti-Static Test



Tear Strength ≥ 120 N



**Bondness Test
 ≥ 4.0 N/mm**



Flex Tester $\geq 36,000$ T

Canton Fair



SAFETY SHOES



RAIN BOOTS



PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY

Production Process



Raw Materials



Punching



Cutting



Riveting



Eyeletting



Sewing



Heat - Setting



Molding



Making up



Finished Goods



Packing



Inspection