

Product Description

Product Name:	High ankle labor protection working safety shoes
Item No:	TM3015
Upper and Sole:	Genuine cow suede leather upper PU dual density sole
Toe cap:	Steel toe cap to be impact resistant 200 joules, Non is also provided. (ASTM F2413-18 M I/75 C/75, CE EN ISO 20345 standard)
Mid sole:	Steel plate to be puncture resistant 1100 newton. Non is also provided. (ASTM F2413-18 M I/75 C/75, CE EN ISO 20345 standard)
Standard:	CE EN ISO 20345 SB-P SRC or others
Style:	Laced up
Collar:	High density oxford fabric
Tongue:	High density oxford fabric
Lining:	Soft air mesh fabric
Sockliner:	Moulded EVA coated with mesh fabric or others
Construction:	PU Injection
Height:	High ankle
Size:	38-46
Guarantee:	6 months
Function:	Slip/ oil/ impact/ puncture resistant, shock absorption, anti static available
Package:	1 pair per color box, 10 pairs per carton. Carton size is 59 x 44 x 33 cm
Load quantity of Container:	3200pairs /1x20' container 6400pairs /1x40' container

Product Pictures





SAFETY SHOES TEST



Toecap Test ≥ 200 Joules



Midsole Test ≥ 1200 Newtons



ESD Anti-Static Test



Tear Strength ≥ 120 N



**Bondness Test
 ≥ 4.0 N/mm**



Flex Tester $\geq 36,000$ T

Canton Fair



SAFETY SHOES



RAIN BOOTS



PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY

[PRODUCTION PROCESS]



Raw Materials



Punching



Cutting



Riveting



Eyeletting



Sewing



Heat - Setting



Molding



Making up



Finished Goods



Packing



Inspection