

Product Description

Nome del prodotto:	Stivali antinfortunistici antinfortunistici da uomo in acciaio con puntale in pelle alta alla caviglia
Oggetto numero:	HA3005
Tomaia e suola:	Tomaia: pelle crosta di mucca gofrata Suola: PU doppia densità
Dito del piede:	1. Puntale in acciaio, può essere resistente agli urti 200 Joule. 2. non è anche previsto.
Intersuola:	1. Lamiera di acciaio, può essere foratura resistente 1100 newton. 2. Non è anche fornito
Peso:	1,2 kg / pr
Collare:	PU pelle artificiale con spugna
Lingua:	Pelle sintetica PU, resistente alla sabbia
Fodera:	Tessuto Air & dry mesh (i tuoi piedi saranno mantenuti asciutti e comodi)
sockliner:	EVA modellato o altri (Riduci notevolmente il dolore e la fatica dal lavoro quotidiano)
Costruzione:	Iniezione PU
Altezza:	Caviglia alta
Taglia:	38-46 EUR (US 4-12)
Standard:	CE EN ISO 20345 SBP SRC o altri come vostre esigenze
Garanzia:	6 mesi
Pacchetto:	1 paio per confezione interna color, 10 paia per cartone.
Dimensioni della scatola	59 x 44 x 33 cm
Carica quantità di container:	Contenitore 3000pairs / 1x20 ' Contenitore 6000pairs / 1x40 '

Product Pictures



Company Information



Intertek

EC Type Examination Certificate

CE	Issued to: FUJIAN HONGJIAN SHISE CO., LTD. SHANGHAI INDUSTRIAL ZONE, JIANGNAN TOWN, NINGBO 321111, ZHEJIANG PROVINCE, CHINA																										
Authorised Representative:	Intertek Asia SAFETY PRODUCTS APC (S) LTD. 1201 Village Square Street, Jersey Science Centre, Paraga Road, Singapore																										
State of Issue:	11 January 2018																										
Expiry Date:	11 February 2020																										
Certificate No.:	LEC170002947 (extension of certificate LEC170294194)																										
Product Reference(s):	<table border="0"> <tr><td>Safety Group:</td><td>1500V</td></tr> <tr><td>Rated Voltage:</td><td>1500V AC</td></tr> <tr><td>Rated Current:</td><td>630A</td></tr> <tr><td>Rated Power:</td><td>945kW</td></tr> <tr><td>Rated Power Factor:</td><td>0.85</td></tr> <tr><td>Rated Frequency:</td><td>50/60Hz</td></tr> <tr><td>Rated Short-Circuit Capacity:</td><td>30kA</td></tr> <tr><td>Rated Short-Circuit Time:</td><td>1s</td></tr> <tr><td>Rated Short-Circuit Energy:</td><td>150MJ</td></tr> <tr><td>Rated Short-Circuit Power:</td><td>1500kVA</td></tr> </table>	Safety Group:	1500V	Rated Voltage:	1500V AC	Rated Current:	630A	Rated Power:	945kW	Rated Power Factor:	0.85	Rated Frequency:	50/60Hz	Rated Short-Circuit Capacity:	30kA	Rated Short-Circuit Time:	1s	Rated Short-Circuit Energy:	150MJ	Rated Short-Circuit Power:	1500kVA						
Safety Group:	1500V																										
Rated Voltage:	1500V AC																										
Rated Current:	630A																										
Rated Power:	945kW																										
Rated Power Factor:	0.85																										
Rated Frequency:	50/60Hz																										
Rated Short-Circuit Capacity:	30kA																										
Rated Short-Circuit Time:	1s																										
Rated Short-Circuit Energy:	150MJ																										
Rated Short-Circuit Power:	1500kVA																										
Description:	<table border="0"> <tr><td>Construction:</td><td>Indoor</td></tr> <tr><td>Topology:</td><td>Open cabinet</td></tr> <tr><td>Mounting:</td><td>Open air</td></tr> <tr><td>Material:</td><td>Steel</td></tr> <tr><td>Color:</td><td>Grey</td></tr> <tr><td>Weight:</td><td>8000 (Typical)</td></tr> <tr><td>Height:</td><td>2000</td></tr> <tr><td>Width:</td><td>1000</td></tr> <tr><td>Depth:</td><td>1000</td></tr> <tr><td>Rated Short-Circuit Capacity:</td><td>30kA</td></tr> <tr><td>Rated Short-Circuit Time:</td><td>1s</td></tr> <tr><td>Rated Short-Circuit Energy:</td><td>150MJ</td></tr> <tr><td>Rated Short-Circuit Power:</td><td>1500kVA</td></tr> </table>	Construction:	Indoor	Topology:	Open cabinet	Mounting:	Open air	Material:	Steel	Color:	Grey	Weight:	8000 (Typical)	Height:	2000	Width:	1000	Depth:	1000	Rated Short-Circuit Capacity:	30kA	Rated Short-Circuit Time:	1s	Rated Short-Circuit Energy:	150MJ	Rated Short-Circuit Power:	1500kVA
Construction:	Indoor																										
Topology:	Open cabinet																										
Mounting:	Open air																										
Material:	Steel																										
Color:	Grey																										
Weight:	8000 (Typical)																										
Height:	2000																										
Width:	1000																										
Depth:	1000																										
Rated Short-Circuit Capacity:	30kA																										
Rated Short-Circuit Time:	1s																										
Rated Short-Circuit Energy:	150MJ																										
Rated Short-Circuit Power:	1500kVA																										

Authorised Representative: Intertek Asia SAFETY PRODUCTS APC (S) LTD.
1201 Village Square Street, Jersey Science Centre, Paraga Road, Singapore

Notified Body: TÜV SÜD
TÜV SÜD Product Certification (UK) Ltd
11th Floor, 100 Brook Street, London, W1D 7LU, UK
TÜV SÜD Group Ltd, 100 Brook Street, London, W1D 7LU, UK

Product Name: CUB
Type: CUB
Rated Voltage: 1500V AC
Rated Current: 630A
Rated Power: 945kW
Rated Power Factor: 0.85
Rated Frequency: 50/60Hz
Rated Short-Circuit Capacity: 30kA
Rated Short-Circuit Time: 1s
Rated Short-Circuit Energy: 150MJ
Rated Short-Circuit Power: 1500kVA

Signature: *C.M.* 15/01/2018

Printed Name: *C.M.* 15/01/2018

Signature: *[Signature]* 15/01/2018

Printed Name: *[Name]* 15/01/2018

This certificate is issued under the supervision of the competent authority of the United Kingdom. It is valid for the purpose of CE marking of the product in accordance with the applicable EU Directives.



Production Process



Raw Materials



Punching



Cutting



Riveting



Eyeletting



Sewing



Heat - Setting



Molding



Making up



Finished Goods



Packing



Inspection

SAFETY SHOES TEST



Toecap Test ≥ 200 Joules



Midsole Test ≥ 1200 Newtons



ESD Anti-Static Test



Tear Strength ≥ 120 N



**Bondness Test
 ≥ 4.0 N/mm**



Flex Tester $\geq 36,000$ T

Canton Fair



SAFETY SHOES



RAIN BOOTS



PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY

2020 INTERSEC

SAFETY SHOES & RAIN BOOTS PROFESSIONAL

