

Product Description

Nome del prodotto:	Scarpe antinfortunistiche in metallo composito senza punta in metallo Tiger Master Master
Oggetto numero:	TH005L
Tomaia e suola:	Tomaia: pelle di mucca goffrata nera Suola: PU doppia densità
Dito del piede:	1. Puntale in composito, può essere resistente agli urti 200 Joule. (punta in acciaio disponibile) 2. non è anche previsto.
Intersuola:	1. Suola intermedia anti-penetrazione non metallica, può essere foratura resistente 1100 newton. (Piastra in acciaio disponibile) 2. Non è anche fornito
Peso:	1,1 kg / pr
Collare:	Tessuto oxford ad alta densità con spugna
Lingua:	Tessuto oxford ad alta densità
Fodera:	Tessuto grigio air & dry in tessuto sandwich (i tuoi piedi saranno mantenuti asciutti e comodi)
sockliner:	EVA o HI-POLY o PU modellati (riducono notevolmente il dolore e la fatica dal lavoro quotidiano)
Costruzione:	Iniezione PU
Altezza:	Caviglia bassa
Taglia:	37-47 (3-13)
Standard:	CE EN ISO 20345 S1P SRC o altri come vostre esigenze
Garanzia:	6 mesi
Pacchetto:	Imballaggio della scatola interna di colore, 10 paia in un cartone.
Dimensioni della scatola	58,5 x 40 x 32,5 cm
Carica quantità di contenitore:	Contenitore 3300pairs / 1x20 ' Contenitore 6600pairs / 1x40 '

Product Pictures





Company Information



Intertek

EC Type Examination Certificate

CE

Issued to:	SHANGHAI HONGJIAN SHIYE CO., LTD. SHANGHAI INDUSTRIAL ZONE, JIANGNAN TOWN, NUSUN 2017, JIANGSU PROVINCE, CHINA																		
Authorised Representative:	Intertek Asia SAFETY PRODUCTS APC (S) LTD. 1001 Village Road, Singapore, Singapore, Singapore																		
Date of Issue:	11 January 2018																		
Expiry Date:	11 January 2020																		
Certificate No.:	LEC170022947 (extension of certificate LEC16284716)																		
Product Reference(s):	Safety Group: 28501-28502 28503-28504 28505-28506 28507-28508 28509-28510																		
Description:	<table border="0"> <tr> <td>Construction:</td> <td>Injection</td> </tr> <tr> <td>Terminal:</td> <td>Open contact</td> </tr> <tr> <td>Material:</td> <td>Open wire</td> </tr> <tr> <td>Lead:</td> <td>2002</td> </tr> <tr> <td>Mark:</td> <td>2002 (Type)</td> </tr> <tr> <td>Mount:</td> <td>ACB</td> </tr> <tr> <td>Test Standard:</td> <td>EN 60947-5-1</td> </tr> <tr> <td>Test Range:</td> <td>28-45</td> </tr> <tr> <td>Category:</td> <td>2002-45A</td> </tr> </table>	Construction:	Injection	Terminal:	Open contact	Material:	Open wire	Lead:	2002	Mark:	2002 (Type)	Mount:	ACB	Test Standard:	EN 60947-5-1	Test Range:	28-45	Category:	2002-45A
Construction:	Injection																		
Terminal:	Open contact																		
Material:	Open wire																		
Lead:	2002																		
Mark:	2002 (Type)																		
Mount:	ACB																		
Test Standard:	EN 60947-5-1																		
Test Range:	28-45																		
Category:	2002-45A																		

CUM

EU

Product Name: 28501-28510
Model No.: 28501-28510
EC Declaration No.: 28501-28510

Product Reference(s): 28501-28510

Product Name: 28501-28510
Model No.: 28501-28510
EC Declaration No.: 28501-28510

Product Reference(s): 28501-28510



Production Process



Raw Materials



Punching



Cutting



Riveting



Eyeletting



Sewing



Heat - Setting



Molding



Making up



Finished Goods



Packing



Inspection

Canton Fair



SAFETY SHOES



RAIN BOOTS



PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY