

Product Description

Nome del prodotto:	S3 stivali S3 SRC High Rigger
Oggetto numero:	TM5009.
Upper e Sole:	Tomaia: pelle di mucca divisa in rilievo Suola: PU / PU Dual Density Sole
Dito del piede:	1. Cap di punta in acciaio per essere resistenti agli urti 200 joule. 2. Viene fornita anche la punta non acciaio.
Intersuola:	1. La piastra in acciaio deve essere resistente alla puntura 1100 Newton. 2. È inoltre fornita la piastra non acciaio
Collare e lingua:	Nessun colletto
stile:	Nessun stivali di saldatura in pizzo
Liner:	Tessuto a maglia d'aria (sarà tenuto i piedi comodi)
Sockliner:	Anti Static Stampato EVA rivestito con tessuto a maglia d'aria o altri come le tue esigenze (riducono notevolmente il dolore e la fatica dal lavoro quotidiano)
Costruzione:	Iniezione di PU
Altezza:	29-30 cm
Dimensione:	38-47.
Standard:	CE EN ISO 20345: 2011 S3P SRC
Garanzia:	6 mesi
Pacchetto:	Imballaggio della scatola interna di colore, 10 coppie in un cartone.
Dimensione del cartone	68 x 65 x 34,5 cm
Quantità di carico del contenitore:	1800 paia / 1x20 'container 3600 paia / 1x40 'Container

Product Pictures





Production Process



Raw Materials



Punching



Cutting



Riveting



Eyeletting



Sewing



Heat - Setting



Molding



Making up



Finished Goods



Packing



Inspection

Canton Fair



SAFETY SHOES



RAIN BOOTS



PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY

SAFETY SHOES TEST



Toecap Test ≥ 200 Joules



Midsole Test ≥ 1200 Newtons



ESD Anti-Static Test



Tear Strength ≥ 120 N



**Bondness Test
 ≥ 4.0 N/mm**



Flex Tester $\geq 36,000$ T