

Product Description

| | |
|-----------|--|
| □□□□ | □□□□□□MILLER STEEL□□□□□□□□□□ |
| □□□□□ | 336BR |
| □□□□□□□□□ | □□□□□PU□□□□□□□□ □□□□□PU□□□□□□□□ |
| □□□□ | 1.□□□□200□□□□□□□□□□□□□□□□ |
| | 2.□□□□□□□□□□□□□□ |
| □□□□□□□ | 1.□□□□□□1100□□□□□□□□□□ |
| | 2.□□□□□□□□□□ |
| □□ | PU□□□□□ |
| □□ | □□□□□□□□□□□□□□ |
| □□□ | □□□&□□□□□□□□□□ |
| □□□ | □□□□□□□□□□□□□□□□□□□□□□EVA |
| □□□ | PU□□ |
| □□□ | □□□□□□ |
| □□□□ | □□□ 38-46 |
| □□□ | SB-P SRC□□□□□□□ |
| □□□ | 6□□ |
| □□□□□□ | □□□□□□□□□□□□□□□□□□□□□□10□□□ |
| □□□□□□□ | 58.5x40x32.5cm |
| □□□□□□□□□ | 3200□□/ 1x20 '□□□□ 6400□□/ 1x40 '□□□□ |

Product Pictures



Production Process



Raw Materials



Punching



Cutting



Riveting



Eyeletting



Sewing



Heat - Setting



Molding



Making up



Finished Goods



Packing



Inspection

SAFETY SHOES TEST



Toecap Test ≥ 200 Joules



Midsole Test ≥ 1200 Newtons



ESD Anti-Static Test



Tear Strength ≥ 120 N



**Bondness Test
 ≥ 4.0 N/mm**



Flex Tester $\geq 36,000$ T

Canton Fair



SAFETY SHOES



RAIN BOOTS



PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY

2020 INTERSEC

SAFETY SHOES & RAIN BOOTS PROFESSIONAL



8-D32