

Product Description

Material	High-density polyethylene
Model	605
Color	White 3D printed
Weight	200g ASTM F2413-18 M I / 75 C / 75 CE EN ISO 20345
Strength	1100g ASTM F2413-18 M I / 75 C / 75 CE EN ISO 20345
Compliance	CE en ISO 20345 SBP SRC
Material	High-density polyethylene
Material	3D printed
Weight	730g
Material	High-density polyethylene
Material	EVA HI-Poly PU
Material	High-density polyethylene
Material	High-density polyethylene
Material	38-46
Material	6
Material	Standard/Custom/Other
Material	1000mm x 1000mm x 58.5 x 40 x 32.5 cm
Material	3300mm / 1x20 'Standard 6600mm / 1x40 'Standard

Product Pictures



PUNCTURE RESISTANT



IMPACT RESISTANT



SUPER LIGHT



Huade®

重量

0.0383

克

去皮

单位

交流

置零

去皮

上海华德衡器有限公司





SAFETY SHOES TEST



Toecap Test ≥ 200 Joules



Midsole Test ≥ 1200 Newtons



ESD Anti-Static Test



Tear Strength ≥ 120 N



**Bondness Test
 ≥ 4.0 N/mm**



Flex Tester $\geq 36,000$ T

Canton Fair



SAFETY SHOES



RAIN BOOTS



PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY