

Product Description

Material	Upper: PU, Sole: PU, CE
Model	6503
Construction	3D, PU
Weight	1. 200g, 2. 200g
Length	1. 110mm, 2. 110mm
Width	3D
Color	
Material	EVA, HIPOLY
Material	
Material	
Material	36-47
Material	CE EN ISO 20345, 2011S1-PSRC
Material	6mm
Material	
Material	1. 10mm, 2. 58.5 X 40 X 32.5 CM
Material	3300mm/1x20", 6600mm/1x40"

Product Pictures



200 JOULE
TOECAP



SLIP-
RESISTANT



SHOCK
ABSORPTION



ANTI-STATIC



PETROL AND
CHEMICAL
RESISTANT



ANTI-NAIL
MIDSOLE



OIL
RESISTANT



[PRODUCTION PROCESS]



Raw Materials



Punching



Cutting



Riveting



Eyeletting



Sewing



Heat - Setting



Molding



Making up



Finished Goods



Packing



Inspection

SAFETY SHOES TEST



Toecap Test ≥ 200 Joules



Midsole Test ≥ 1200 Newtons



ESD Anti-Static Test



Tear Strength ≥ 120 N



**Bondness Test
 ≥ 4.0 N/mm**



Flex Tester $\geq 36,000$ T

Canton Fair



SAFETY SHOES



RAIN BOOTS



PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY