

□□□□	□□□□□□□□□□□□□□□□
□□□□□	3098
□□□□□□□□	□□□□□PU□□□□□□□□
□□□	1.□□□□□□□□□□□□□□□□ □ASTM F2413-05 M I / 75 C / 75□CE ENISO 20345 STANDARD□□□□□ □□□□□ □□□□□
	2.□□□□□□□□□□
□□ □ □□□□□□□□	1.□□□□□□□□□□□□□□ □ASTM F2413-05 M I / 75 C / 75□CE ENISO 20345 STANDARD□□□□□□□□□□□□□□
	2.□□□□□□□□
□□□	PU□□□□ □□□□□□□□□□□
□□	□□□□PU
□□	□□□□□□□□□□
□□□	□□□□□□
□□□	PU □□
□□□	□□□□□
□□□	4□12□□38-46□
□□□	3□□□□□□□□□□□□□□
□□□□□	□□□□□□□□□□□□□□□□10□
□□□□□□	56x38x31.5cm □38-40□; 58.5x40x32.5cm□41-43□; 61x42x35cm□44-46□
□□□□□□□□	3300pairs / 1x20 '□□□□ 8200pairs / 1x40 'HQ□□□□

□□□□□□□□□□□□□□□□□□□□□□



□□□□□□□□□□□□□□□□□□□□□□□□



10 of 10



████████████████████████

