

□□□□	2018□□□□□□□□+□□□□□□□□□□□□
□□□□□	DTA012
□□□□□□□□	□□□□□□□□PU□□□□□□□□□□
□□□□	1.□□□□□□□□□□□□□□ □ASTM F2413-05 M I / 75 C / 75□CE ENISO 20345 STANDARD□ □□□□□□□ □□□□□□□□
	2.□□□□□□□□□□□□□□
□□□□□	1.□□□□□□□□2□ □ASTM F2413-05 M I / 75 C / 75□CE ENISO 20345 STANDARD□□□□□□□□□□□□□□□□□□□□□□□□
	2.□□□□□□□□□□
□□	PU□□□□
□□	PU□□□□
□□□	□□ □□□□□□□□□□ □□□□□□□□□□ □□□□□□□□□□□□□□
□□□□□□□□	□□□□□□□□□□□□□□EVA
□□□	PU□□
□□□	□□□□
□□□□	4-12□38-46□
□□□	3 □□□□□□□□□□□□□□
□□□□□□	□□□□□□□□□□□□□□□□□□□□□□□□10□□
□□□□□□□□	58.5x40x32.5cm
□□□□□□□□□□	3300□□/ 1x20 '□□□□□ 6600□□/ 1x40 '□□□□□

□□□□□□□□□□



□□□□□□□□□□

