

Product Description

Model	DTA032H
Material	1. 200 PU 2. non
Weight	1.2 kg / pr
Dimensions	59 x 44 x 33 cm
Color	10
Material	EVA HI-POLY PU
Material	PU
Material	
Material	&
Material	EVA HI-POLY PU
Material	PU
Material	
Material	37-47 3-13
Material	CE EN ISO 20345 S1P SRC
Material	6
Material	c 1 olor 10
Material	59 x 44 x 33 cm
Material	3200 / 1x20 6400 / 1x40

Product Pictures





Company Information



Intertek

EC Type Examination Certificate



Issued to: FUJIAN HONGJIAN SHISEI CO., LTD.
SHANGHAI INDUSTRIAL ZONE, JIANGNAN TOWN, NINGBO
321117, ZHEJIANG PROVINCE, CHINA

Authorised Representative: HANDEHU SHANGHAI ELECTRICITY APPL. CO., LTD.
1201 Village, Xujiao Town, Jiangyin District, Suzhou,
Henanjiang Province, China

Date of Issue: 11 January 2018

Expiry Date: 11 February 2020

Certificate No.: L20170002947 (extension of certificate L20170294719)

Product Reference(s): Safety Group:
480V-1000V
480V-1000V
480V-1000V
480V-1000V
480V-1000V
480V-1000V

Description:

Construction:	Insulation
Terminal:	Open terminal
Material:	Open wire
Core:	0.50
Wire:	0.50 (PVC)
Mark:	AC0
Test frequency:	See technical file
Test range:	0.5A
Category:	001-01A

C.M. 1687-0218

 **Product Approval** 1687-0218

Intertek Testing Services (UK) Limited, 35 Littlefield Way, Borehamwood, Hertfordshire, SG9 6ND, UK



Production Process



Raw Materials



Punching



Cutting



Riveting



Eyeletting



Sewing



Heat - Setting



Molding



Making up



Finished Goods



Packing



Inspection

SAFETY SHOES TEST



Toecap Test ≥ 200 Joules



Midsole Test ≥ 1200 Newtons



ESD Anti-Static Test



Tear Strength ≥ 120 N



**Bondness Test
 ≥ 4.0 N/mm**



Flex Tester $\geq 36,000$ T

Canton Fair



SAFETY SHOES



RAIN BOOTS



PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY