Product Description

□□□□	□□□□□□□PU□□□□□□□□□□□□□□□□□□□□□□□□□
□□□□□	DTA038
□□□□□□□□□	□□□□□□□□□□□□□ □□□□PU / PU□□□□□□□□□□□□□□□□
□□□□	1.□□□□□□□□□□□□□□□□□□□200□□□□□
	2. non□□□□□□□□□
□□□□□□□	1□ □□□ □□□ □□ □□□□□ 1100 □□□□□□ 2□ □□ □□ □□ □□
□□□	1.1 kgs / pr
□□	□□□□□□□
□□	□□□□□□□
□□□	□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□
□□□□	□□EVA□□□HI-POLY□□□PU□□□□□□□□□□□□□□□□□□□□□□
□□□	PU□□□□□□□□
□□□	□□□□□
□□□□	37-47□3-13□
□□□	□□□□□CE EN ISO 20345 SB-P SRC□□□□□□
□□□	6□□
□□□□□□	C□□□1□□olor□□□□□□□□□□□□□□□□□□□□□□□10□□□
□□□□□□□	58.5 x 40 x 32.5 cm
□□□□□□□□□	3300□□/ 1x20 '□□□□ 6600□□/ 1x40□□□□

Product Pictures

Company Information

Intertek

EC Type Examination Certificate

CE

Issued to:

Authorised Representative:

Date of Issue:

Expiry Date:

Certificate No.

Product Reference(s):

Description:

Production Process

Raw Materials

Punching

Cutting

Sewing

Eyeletting

Riveting

Heat - Setting

Molding

Making up

Inspection

Packing

Finished Goods

SAFETY SHOES TEST

Toecap Test≥200 Joules

Midsole Test≥1200 Newtons

ESD Anti-Static Test

Tear Strength ≥120N

Bondness Test
≥4.0N/mm

Flex Tester ≥ 36,000T

SHOES MATERIALS

Genuine Cow Leather

CE Steel Toecap

CE Steel Plate


Composite Toecap

Different Eyelets

Durable Lace

Breathable Lining

Comfortable Insoles

PU or RUBBER or TPU soles

Canton Fair

SAFETY SHOES

RAIN BOOTS

PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY