Product Description

□□□□	□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□
□□□□□	ENS032G
□□□□□□□□□□	□□□□□□□□□□□□□□□□ PU / PU□□□□□□□
□□□□□□□□□□	□□□□□□□□□□□□200□□□□□□□□□□□□□□□□□□□□□□□□ □ASTM F2413-18 M I / 75 C / 75□CE EN ISO 20345□□□ □□□□□□□□□□□□□□□□
□□□□□□□□	□□□□□□□□□□□□1100□□□□□□□□□□□□□□□□□□□□□□□□ □ASTM F2413-18 M I / 75 C / 75□CE EN ISO 20345□□□ □□□□□□□□□□□□□□□□
□□□	CE EN ISO 20345 S1-P SRC□□□□□□□
□□□□	□□□□□□□□
□□	□□□□□□
□□	□□□□□□&□□□□□□□□
□□□	□□□□□□□□□□□□□□□□
□□□□	□□EVA□□□HI-POLY□□□PU
□□□	PU□□□
□□□	□□□□
□□□□	38□46□□□
□□□	6 □□
□□□	□□□□/□□□/□□/□□□□□□□□□□□□□□□□
□□□□□□	□□□□□□□□□□□1□□□□□□□□□□□10□□□□□□□□□□□□ 59 x 44 x 33 cm
□□□□□□□□□□	3200□□/ 1x20 '□□□□ 6400□□/ 1x40□□□□

Product Pictures

Production Process

Raw Materials

Punching

Cutting

Sewing

Eyeletting

Riveting

Heat - Setting

Molding

Making up

Inspection

Packing

Finished Goods

SAFETY SHOES TEST

Toecap Test≥200 Joules

Midsole Test≥1200 Newtons

ESD Anti-Static Test

Tear Strength ≥120N

Bondness Test
≥4.0N/mm

Flex Tester ≥ 36,000T

Canton Fair

SAFETY SHOES

RAIN BOOTS

PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY